



| | | | Description |
|-----|---------------------|-----|---|
| | 33311B | | Cylinder (Incl. 2,3,4,5,184) (2-5/8" Bore) |
| 2 | 27652 | F | Pin, Dowel |
| 3 | 27642 | F | Plug, Oil drain, 1/4-18 |
| 4 | 27876B | , | Seal, Oil |
| 5 | 32783 | I | Intake Valve (Std.) (Incl. 9) |
| 5 | 32784 | I | Intake Valve (1/32" OS) (Incl. 9) |
| 6 | 27878A | - 1 | Exhaust Valve (Std.) |
| 6 | 27880A | - 1 | Exhaust Valve (1/32" OS) (Incl. 9) |
| 7 | 27882 | (| Cap, Upper valve spring |
| | 27881 | | Spring, Valve |
| | 32581 | | Cap, Lower valve spring |
| | 30799 | | Crankshaft (Incl. 12 & 13) |
| | 29783 | | Pin, Crankshaft gear Used in early production. This gear is |
| | | | serviceable ONLY when itis pinned to the crankshaft. |
| 13 | 27884 | | Gear, Crankshaft Used in early production. This gear is |
| | | | serviceable ONLY when itis pinned to the crankshaft. |
| | 34531 | | Piston, Pin & Ring Set (Std.) (2-5/8" Bore) |
| | 34532 | | Piston, Pin & Ring Set (.010" OS) |
| | 34533 | | Piston, Pin & Ring Set (.020" OS) |
| | 33312B | | Piston & Pin Ass'y. (Std.)(2-5/8")(In cl.16) |
| | 33313B | | Piston & Pin Ass'y. (.010" OS) (Incl. 16) |
| | 33314B | | Piston & Pin Ass'y. (.020" OS) (Incl. 16) |
| | 34854 | | Ring Set (Std.) (2-5/8" Bore) |
| | 34855 | | Ring Set (.010" OS) |
| 15 | 34856 | F | Ring Set (.020" OS) |
| 16 | 27888 | F | Ring, Piston pin retaining |
| 17 | 31380C | F | Rod Assy., Connecting (Incl. 18) |
| 18A | 30682 | | Bolt, Connecting rod (Early productio n) |
| 18 | 650662C | | Screw, Connecting rod (Late productio n) |
| 19 | 26073 | | Connecting rod bolt washer (Early pro duction) |
| | 28264 | | Connecting rod nut (Used on early pro duction) |
| | 33156 | | Camshaft |
| | 34034 | | Lifter, Valve |
| | 31303B | | Cover, Cylinder (Incl. 24, 27 & 105) |
| | 28427 | | Seal, Oil |
| | 30684 | | * Gasket, Cylinder cover |
| | 31546 | | Bushing, Crankshaft |
| | 650488 | | Screw, 1/4-20 x 1-1/4" |
| | 650493 | | Screw, 1/4-20 x 1-3/4" |
| | 650489 | | Screw, 1/4-20 x 5/8" |
| | 30939A | | Cover, Cylinder head |
| | 28938C | | * Gasket, Cylinder head |
| | 30938A | | Head, Cylinder (Incl. 3 of 36) |
| | 33636 | | Resistor Spark Plug |
| | 26073 | | Washer, Flat (Use as required) |
| | 650570 | | Washer, Flat (Use as required) |
| | 650691 | | Washer, Flat (Use as required) |
| | | | |
| | 650697A 650606 A | | Screw, 5/16-18 x 2-1/2" (Use as required) |
| | 650695A 650604A | | Screw, 5/16-18 x 2-1/4" (Use as required) |
| | 650694A | | Screw, 5/16-18 x 2" (Use as required) |
| | 650128 | | Screw, 10-24 x 1/2" (Use as required) |
| | 650597 | | Screw, 10-24 x 5/8" (Use as required) |
| | 27896A | | * Gasket, Breather cover |
| | 28423 | | Body, Breather |
| | 28424 | | Element, Breather |
| | 28425 | | Cover, Valve spring |
| 45 | 27915A | , | * Gasket, Intake |

| | Part Number 30195A | Qty | Description Flange, Carburetor (Incl. 79 & 80) |
|----------|-----------------------|-----|--|
| | | | · , |
| | 30196 | | Screw, 5/16-18 x 3/4" |
| | 29918 | | Lockwasher |
| 50 | 650548 | | Screw, 8-32 x 5/16" |
| 51 | 30319 | | Rivet, Split (Used on early productio n) |
| | 32326A | | Lever, Governor (New lever does not need 1 of Ref |
| <u> </u> | 02020, 1 | | #49,51,53,54,132,133) |
| 52 | 30322 | | • |
| | | | Lock Nut, 8-32 (Use as required) |
| | 29916 | | Clamp, Governor lever (Use as require d) |
| | 30205 | | Bracket, Adjusting |
| 56 | 31710 | | Link, Throttle |
| 58 | 29216 | | Locknut, 10-32 |
| 59 | 29752 | | Nut & Lockwasher, 1/4-28 |
| | 650572 | | Screw, 1/4-28 x 1-1/8" |
| | 29826 | | Screw, 10-32 x 3/4" |
| | | | |
| | 29642 | | Ring, Retaining |
| | 30699C | | Rod Assy., Governor (Incl. 64 & 65) |
| 63 | 30699B | | Rod Assy., Governor (This one piece gov. rod is no longer |
| | | | used. It is replaced by 30699C assy., Ref.#63A) |
| 64 | 30700 | | Yoke, Governor |
| | 650494 | | Screw, 6-40 x 5/16" |
| | 31297 | | Dipstick (Incl. 68) |
| | 29673 | | * Gasket, Dipstick |
| | 29747B | | |
| | | | Screw, 5/16-24 x 21/32" Player Hag. (For also starter)(Incl.4.80.400) |
| | 32158E | | Blower Hsg. (For elec.starter)(Incl.1 89,190) |
| | 29536 | | Baffle, Blower housing |
| | 650561 | | Screw, 1/4-20 x 5/8" |
| | 31688A | | * Gasket, Carburetor |
| 81A | 650152 | | Screw, 8-32 x 3/8" |
| 81 | 30196 | | Screw, 5/16-18 x 3/4" (Use as require d) |
| 81 | 28820 | | Screw, 10-32 x 1/2" (Use as required) |
| 81 | 650521 | | Screw, 10-32 x 1-1/8" (Use as require d) |
| | 27272A | | * Gasket, Air cleaner |
| | 31691 | | Bracket, Air cleaner |
| | 30727 | | Element, Air cleaner |
| | 31715 | | Body, Air cleaner |
| | 730127 | | |
| 09 | 130121 | | Air Cleaner Ass'y. (Incl. 81,81A,82,83,84,85,90G & 298B) |
| | | | (Use as required) |
| 98 | 28569 | | Compression Spring (Used with 29500 screw)(Use as |
| | | | required) |
| 98 | 32924 | | Compression Spring (Used with 650688 screw) (Use as |
| | | | required) |
| 00 | 04040 | | |
| 98 | 31342 | | Compression Spring (Used with 650549 screw) (Use as |
| | | | required) |
| 99 | 650549 | | Screw, 5-40 x 7/16" (Use as required) |
| 99 | 29500 | | Screw, 8-32 x 3/4" (Use as required) |
| | 650688 | | Screw, 10-32 x 1 (Use as required) |
| | 30884 | | Key, Flywheel |
| | 31843A | | Bracket, Governor gear |
| | 650836 | | |
| | | | Screw, 10-24 x 1/2" |
| | 31845 | | Shaft, Mechanical governor |
| | 30590A | | Washer, Flat |
| | 30591 | | Gear Assy., Governor (Incl. 106) |
| | 30588A | | Spool, Governor |
| 109 | 29193 | | Ring, Retaining |
| | | | - - |

| Ref # | Part Number | Qty | Description |
|-------|-------------|-----|---|
| 111D | 34158 | • | Bracket, Lower fuel tank |
| 112 | 34159 | | Plate, Upper fuel tank mtg. |
| | 650665 | | Screw, 1/4-15 x 3/4" |
| | 650561 | | Screw, 1/4-20 x 5/8" |
| | 34186A | | Fuel Tank (Incl. 115 & 120) |
| | 410144B | | Fuel Cap (White Plastic)(Standard)(As req.) |
| | 33032 | | Fuel Cap (Red Plastic) (Spurt Resistant, Low Profile) (Use |
| 110 | 30002 | | as required) |
| | | | as required) |
| 115 | 34210 | | Fuel Cap (Red Plastic) (Spurt Resistant, High Profile) (Use |
| | | | as required) |
| 440 | 00774 | | . , |
| | 29774 | | Fuel Line (Braided 8.25") (Use as req uired) |
| | 30705 | | Fuel Line (Braided 16") (Use as requi red) |
| | 30962 | | Fuel Line (Braided 32") (Use as requi red) |
| | 26460 | | Clamp, Fuel line (Use as required) |
| | 27930A | | * Gasket, Exhaust |
| | 650548 | | Screw, 8-32 x 5/16" (Early production) |
| | 650139 | | Screw, 8-32 x 1/2" (Early production) |
| 144 | 650542 | | Screw, 5/16-18 x 3/4" |
| 146 | 29538 | | Base, Engine mounting |
| 147 | 650128 | | Screw, 10-24 x 1/2" |
| 148 | 30622A | | Extension, Blower housing |
| 149A | 30747 | | Clip, Shorting |
| 150 | 650890 | | Lockwasher |
| 186 | 27275 | | Clip, Wire (Use as required) |
| | 29443 | | Clip, Fuel line (Use as required) |
| | 31386 | | Spring, Extension |
| | 31711B | | Control Bracket (Incl. 98, 99 & 226) |
| | 610973 | | Terminal Assy. |
| | 28942 | | Screw, 10-32 x 3/8" |
| | 27793 | | Clip, Conduit |
| | 35349 | | Ground Wire |
| | 29716 | | Screw, 1/4-28 x 7/16" |
| | 32125 | | Cup, Starter |
| | 590417 | | Screen, Starter cup |
| | 650815 | | · · · · · · · · · · · · · · · · · · · |
| | | | Washer, Belleville |
| | 8116 | | Nut, Hex |
| | 34346 | | Decal, Instruction |
| | 31752 | | Decal, Air cleaner |
| | 550223 | | Decal, Name |
| | 33310 | | Decal, 5 HP Mini-Bike (Use as require d) |
| | 31517 | | Decal, H.P. (5 H.P.) (Use as required) |
| | 32173 | | Decal, H.P. (6 H.P.) (Use as required) |
| | 30547A | | Contact Assy., Breaker |
| | 30548B | | Condenser |
| | 631021 | | Inlet Needle, Seat & Clip Assy. |
| 303 | 631828 | | Carburetor (Incl. 75 & 301) (Refer to Division 5, Section A, |
| | | | page 144 for breakdown) |
| 304 | 610689A | | Magneto NOTE: The complete magneto is not available as |
| 304 | 010003A | | an assembly. The magneto number is shown for reference |
| | | | |
| | | | purposes only. Order component parts individually, as |
| | | | shown in parts list. (Refer to Division 5, Section B, page 24 |
| | | | for breakdown) |
| 306 | 590420 | | Rewind Starter (Refer to Division 5, Section C, page 25 for |
| | | | breakdown) |
| 040 | 22225 | | , |
| 310 | 33235A | | * Gasket Set (Incl. items marked *) |
| | | | |



| Ref # | Part Number | Qty | Description |
|-------|-------------|-----|--|
| 35 | 26073 | | Washer, Flat (Use as required) |
| 35 | 650570 | | Washer, Flat (Use as required) |
| 35 | 650691 | | Washer, Flat (Use as required) |
| 36 | 650697A | | Screw, 5/16-18 x 2-1/2" (Use as requi red) |
| 36 | 650695A | | Screw, 5/16-18 x 2-1/4" (Use as requi red) |
| 36 | 650694A | | Screw, 5/16-18 x 2" (Use as required) |
| 38 | 27896A | | * Gasket, Breather cover |
| 81 | 30196 | | Screw, 5/16-18 x 3/4" (Use as require d) |
| 81 | 28820 | | Screw, 10-32 x 1/2" (Use as required) |
| 81 | 650521 | | Screw, 10-32 x 1-1/8" (Use as require d) |
| 82 | 27272A | | * Gasket, Air cleaner |
| 86A | 34697 | | Air Cleaner Elbow Assy.(Use in 730561 only.) |
| 89A | 730128 | | Air Cleaner Ass'y. (Incl. 82,90A,90B,90D thru 90G,97 & |
| | | | 298B) (Use as req.) |
| | 650665 | | Screw, 1/4-15 x 3/4" |
| 121E | 391026 | | Muffler (Incl. 124, 124A & 124B) (This spark arrester |
| | | | mufflercan be used on any model) |
| 121A | 29633 | | Muffler |
| 124A | 33171 | | Muffler Screen (Use as required) |
| 124B | 33185 | | Cover & Tube, Muffler (Use as require d) |
| 124 | 650578 | | Screw, 8-18 x 3/8" |
| 125 | 27930A | | * Gasket, Exhaust |
| 129 | 32862 | | Nut, Conduit (1/4" thick) |
| | 30244 | | Nipple, Pipe (2.5") |
| 131 | 30209 | | Elbow, Exhaust (45 degree) |
| | 31288 | | Muf.Adapter Kit(Incl.125,136,137)(As req.) |
| | 730130 | | Muf.Adapter Kit(Incl.125 & 138)(As re quired) |
| | 6021A | | Screw, 5/16-18 x 1-1/2" (Use as requi red) |
| | 650697A | | Screw, 5/16-18 x 2-1/2" (Use as requi red) |
| 138 | 30196 | | Screw, 5/16-18 x 3/4" (Use as require d) |
| 233 | 34819 | | Air Cleaner Elbow (Incl.44,76,78,83A,86A,100)(Use in |
| | | | 730561 ass'y. only) |
| 234 | 730561 | | Air Cleaner Kit |
| | | | (Incl.38,43,44,76,78,79,82,83A,84,84C,86A,87,90,100A,233,29) (Use only on engines with an externally ventedfully |
| | | | adjustable carburetor.) |
| 273 | 650687 | | Screw, 10-32 x 5/16" (Use as required) |
| | | | |



| | | Qty | Description |
|-----|--------|-----|--|
| | 650128 | | Screw, 10-24 x 1/2" (Use as required) |
| 37 | 650597 | | Screw, 10-24 x 5/8" (Use as required) |
| 37A | 27261 | | Washer, Flat (Use as required) |
| 41 | 28425 | | Cover, Valve spring |
| 43A | 35350 | | Tube, Breather |
| | 31710 | | Link, Throttle |
| | 29747B | | Screw, 5/16-24 x 21/32" |
| | 28569 | | Compression Spring (Used with 29500 screw)(Use as |
| 00 | 25000 | | required) |
| 98 | 32924 | | Compression Spring (Used with 650688 screw) (Use as |
| | | | required) |
| 98 | 31342 | | Compression Spring (Used with 650549 screw) (Use as |
| | | | required) |
| 99 | 650549 | | Screw, 5-40 x 7/16" (Use as required) |
| 99 | 29500 | | Screw, 8-32 x 3/4" (Use as required) |
| 99 | 650688 | | Screw, 10-32 x 1 (Use as required) |
| 182 | 32683A | | Gasket, Fuel pump cover (Use as required) |
| 183 | 32955 | | Cover, Fuel pump pad (Use as required) |
| 184 | 9556 | | Plug, Pipe 1/8-27 (Use as required) |
| 185 | 30063 | | Screw, 1/4-20 x 1/2" (Use as required) |
| | 28545 | | Grommet, Plastic |
| | 650760 | | Screw, 8-32 x 3/8" |
| | 33356 | | Terminal, Ground |
| | 730152 | | Control Bracket(Incl.91 thru 97)(As r eq.) |
| | 610973 | | Terminal Assy. |
| | 33177 | | Terminal (Use as required) |
| | 28942 | | Screw, 10-32 x 3/8" |
| | 27793 | | Clip, Conduit |
| | 29716 | | Screw, 1/4-28 x 7/16" |
| | 650815 | | Washer, Belleville |
| | 8116 | | Nut, Hex |
| | 33018 | | Harness Assy., Adapter (Use as required) |
| | 590420 | | Rewind Starter (Refer to Division 5, Section C, page 25 for |
| 300 | 350420 | | breakdown) |
| 308 | 33328D | | Starter Motor Kit (110-120 Volt) NOTE: This 110-120 volt |
| | | | starter motor kit may have been added to this engine. This can be added only if cylinder has drilled and tapped starter mounting bosses and a ring gear flywheel has been added (see #309). Refer to service number stamped on end cap of motor, |
| 309 | 30811A | | Flywheel (Ring gear flywheel requiredon engines using 110-120 volt starter motor kits listed above.) |
| | | | |