

|     |                  | Qty | Description  |
|-----|------------------|-----|--|
| 1   | 34919A           |     | Cylinder (Incl. 2,3 & 4) (2-5/8" Bore )                    |
| 2   | 27652            |     | Pin, Dowel   |
| 3   | 27642            |     | Pipe plug, 1/4-18  |
| 4   | 32630            |     | Seal, Oil  |
|     | 29536            |     | Blower Housing Baffle (Without electric starter knock out) |
| · · |                  |     | (Use as required)  |
| _   |                  |     | ,  |
| 5   | 35256A           |     | Blower Housing Baffle (With electric starter knockout) (As |
|     |                  |     | req.)(point ign.)  |
| 6   | 650561           |     | Screw, 1/4-20 x 5/8"                                       |
|     | 29538            |     | Base, Engine mounting                                      |
|     | 650542           |     | Screw, 5/16-18 x 3/4"                                      |
|     | 34872            |     | Crankshaft   |
|     | 29783            |     | Pin, Crankshaft gear (Used on early p rod.)                |
|     | 27884            |     | Gear, Crankshaft (Used on early production) This gear is   |
| 11  | 27004            |     | serviceable ONLY when it is pinned to the crankshaft.      |
|     |                  |     | serviceable ONLT when it is pillified to the clarifishalt. |
| 13  | 34531            |     | Piston, Pin & Ring Set (Std.) (2-5/8" Bore)                |
| 13  | 34532            |     | Piston, Pin & Ring Set (.010" OS)                          |
| 13  | 34533            |     | Piston, Pin & Ring Set (.020" OS)                          |
| 13A | 33312B           |     | Piston & Pin Ass'y. (Std.)(2-5/8")(In cl.14)               |
| 13A | 33313B           |     | Piston & Pin Ass'y. (.010" OS) (Incl. 14)                  |
|     | 33314B           |     | Piston & Pin Ass'y. (.020" OS) (Incl. 14)                  |
|     | 27888            |     | Ring, Piston pin retaining                                 |
|     | 34854            |     | Ring Set (Std.) (2-5/8" Bore)                              |
|     | 34855            |     | Ring Set (.010" OS)  |
|     | 34856            |     | Ring Set (.020" OS)  |
|     | 31380C           |     | Rod Assy., Connecting (Incl. 17)                           |
|     | 650662C          |     | Bolt, Connecting rod (Incl. 2 pieces)                      |
|     | 34034            |     | Lifter, Valve  |
|     | 30622A           |     | Extension, Blower housing                                  |
|     | 650128           |     | Screw, 10-24 x 1/2"  |
|     | 650561           |     | Screw, 1/4-20 x 5/8" (Use as required )                    |
|     | 30063            |     | Screw, 1/4-20 x 1/2" (Use as required )                    |
|     | 30684            |     | Gasket Cylinder Cover                                      |
|     | 31303B           |     | Cover, Cylinder (Incl. 26 & 34)                            |
|     | 31546            |     | Bushing, Crankshaft  |
|     | 28427            |     | Seal, Oil  |
|     | 650488           |     | Screw, 1/4-20 x 1-1/4"                                     |
|     | 650493           |     | Screw, 1/4-20 x 1-3/4"                                     |
|     | 30699C           |     | Rod Assy., Governor (Incl. 30 & 31)                        |
|     | 30700            |     | Yoke, Governor   |
|     | 650494           |     | Screw, 6-40 x 5/16"  |
|     | 29642            |     | Ring, Retaining  |
|     | 31845            |     | Shaft, Mechanical governor                                 |
|     | 30588A           |     | Spool, Governor  |
|     | 35479            |     |  |
|     |                  |     | Washer, Flat   |
|     | 29193            |     | Ring, Retaining  |
|     | 30591            |     | Gear Assy., Governor                                       |
|     | 31843A<br>650936 |     | Bracket, Governor gear                                     |
|     | 650836           |     | Screw, 10-24 x 1/2"  |
|     | 32783            |     | Intake Valve (Std.)  |
|     | 32784            |     | Intake Valve (1/32" OS)                                    |
|     | 27878A           |     | Exhaust Valve (Std.)                                       |
|     | 27880A           |     | Exhaust Valve (1/32" OS)                                   |
|     | 27882            |     | Cap, Upper valve spring                                    |
|     | 27881            |     | Spring, valve  |
| 45  | 32581            |     | Cap, Lower valve spring                                    |
|     |                  |     |  |

|     | Part Number Qty | •   |
|-----|-----------------|---|
| 46  | 33876           | Gasket, Stator  |
| 47  | 650489          | Screw, 1/4-20 x 5/8"  |
|     | 34235           | Ground Wire   |
|     | 32589           | Key, Flywheel   |
|     | 28938C          | Gasket, Cylinder head   |
|     | 30938A          |   |
|     |                 | Head, Cylinder  |
|     | 33636           | Resistor Spark Plug (RJ-8C)                                     |
|     | 610118          | Cover, Spark plug (Use as required)                             |
|     | 30939A          | Cover Assy., Cylinder head                                      |
|     | 650697A         | Screw, 5/16-18 x 2-1/2" (Use as requi red)                      |
|     | 650694A         | Screw, 5/16-18 x 2" (Use as required)                           |
| 56  | 650695A         | Screw, 5/16-18 x 2-1/4" (Use as requi red)                      |
| 56A | 650691          | Washer, Flat (Use as required)                                  |
| 56B | 650690          | Washer, Belleville (Use as required)                            |
| 57  | 29916           | Clamp, Governor lever (Use as require d)                        |
|     | 30322           | Locknut, 8-32   |
|     | 32326A          | Lever, Governor   |
|     | 29918           | Washer, Lock, No. 8 E.T.  |
|     | 30205           | Bracket, Governor adjusting                                     |
|     | 650548          | Screw, 8-32 x 5/16"   |
|     | 29216           |   |
|     |                 | Locknut, 10-32  |
|     | 29826           | Screw, 10-32 x 3/4"   |
|     | 31386           | Spring, Extension   |
|     | 31710           | Link, Throttle  |
|     | 31711B          | Control Bracket (Incl. 68, 69 & 72)                             |
|     | 29500           | Screw, 8-32 x 3/4"  |
|     | 27793           | Clip, Conduit   |
| 71  | 28942           | Screw, 10-32 x 3/8"   |
| 72  | 610973          | Terminal Assy. (Use as required)                                |
| 74  | 27896A          | Gasket, Valve chamber cover                                     |
| 75  | 28423           | Breather Assy., Valve   |
|     | 28424           | Element, Breather   |
|     | 28425           | Cover, Valve spring box   |
|     | 650128          | Screw, 10-24 x 1/2"   |
|     | 35350           | Tube, Breather  |
|     | 32446           | Grommet, Breather tube  |
|     | 27915A          | * Gasket, Intake pipe to cylinder                               |
|     | 34712           | • • •   |
|     |                 | Flange, Carburetor (Incl. 86A)                                  |
|     | 30196           | Screw, 5/16-18 x 3/4"   |
|     | 31688A          | * Gasket, Carburetor  |
|     | 650517          | Screw, 1/4-20 x 13/16"  |
|     | 27272A          | * Air Cleaner Gasket (Use as required)                          |
|     | 30767           | Spacer, Cleaner (Use as required)                               |
| 94A | 34819           | Elbow Assy., Air cleaner (Incl. 90,91,92,93,94,96) (Use in      |
|     |                 | 730561 assembly only)   |
| 101 | 24150           | Product Fuel took   |
|     | 34158<br>650665 | Bracket, Fuel tank  |
|     | 650665          | Screw, 1/4-14 x 7/8"  |
|     | 34159           | Plate, Fuel tank mounting                                       |
| 104 | 34186A          | Fuel Tank (Incl. 105 & 107) NOTE: These tanks were built        |
|     |                 | with different size fuel inlet openings. Tanks with the 1-3/16" |
|     |                 | I.D. opening use fuel cap 33032 or 34210. Tanks with the        |
|     |                 | 1-1/2" I.D. opening use fuel cap 35355.                         |
| 105 | 410144B         | Fuel Cap (White Plastic)(Std.)(As req uired)                    |
|     |                 |   |
| 105 | 33032           | Fuel Cap (Red Plastic) (Spurt resistant, Low profile) (Use as   |
|     |                 | required)   |

| Ref # Part Number   | Qty Description  |
|---|--|
| 105 34210   | Fuel Cap (Red Plastic) (Spurt resistant, High profile) (Use as required)   |
| 105 35355 106 29774 106 30962 107 26460 108 32158E 109 29747B 110 27930A 111C 391026 111 32401 111D 33714 111E 34390 112 30196 113 26073 114 650694A 115 32125 116 35009 117 650815 118 8116 119 29716 120 31708 121 28820 122 31700 123 31715 124 650152 143 650578 143A 33171 143B 33185 144 33700 144A 33323 | required)  Fuel Cap (Red plastic) (Use as requir ed) Fuel Line (Braided, 8 1/4") (Use as r equired) Fuel Line (Braided, 32") (Use as required) Clamp, Fuel line (Use as required) Blower Housing (For electric starter) Screw, 5/16-24 x 21/32"  * Gasket, Exhaust flange Opt.Spark Arrest Muf.(Incl.143,143A,1 43B) Muffler Opt.Spark Arrest Muf.(Incl.112,143,14 4,144A) Deflector, Exhaust (Optional) Screw, 5/16-18 x 3/4" Washer, Flat Screw, 5/16 - 18 x 2" Cup, Starter Screen, Starter cup Washer, Belleville Nut, Hex Screw, 1/4-28 x 7/16" Bracket, Air cleaner Screw, 10-32 x 1/2" Element, Air cleaner Body, Air cleaner Screw, 8-32 x 3/8" Screw, 8-18 x 3/8" (Use as required) Screen, Muffler (Use as required) Cover & Tube, Muffler (Use as require d) Screen, Muffler (Use as require d) Screen, Muffler (Use as require d) Screen, Muffler (Use as require d) |
| 145 31297<br>146A 29673<br>200 30208<br>201A 730130<br>201B 730561  | Dipstick (Incl. 146A)  * Gasket, Oil fill  Bracket, Choke control  Muffler Adapter Kit (Incl.110,112)(As req.)  Air Cleaner Kit  (Incl.74,79,80,87,88,89,90,91,92,94,95,96,97,99,100 & 230C)  (Used only on engine with an externally vented fully adjustable carburetor)  |
| 201 730164  | Air Cleaner Ass'y. (Red Poly)(Incl.87,120,121,122,123,124 & 230)(As req.)  |
| 201 730164  | Air Cleaner Kit, Mini bike (Incl.87,120,121,122,123 & 124) (Use as required)   |
| 231A 30548B<br>231 30547A<br>232A 631021<br>240 611077<br>241 650868<br>242 611078<br>242 611079<br>243 590610<br>244 590613<br>250 632230  | Condenser Breaker Assy (Used on Std. Point igni tion) Inlet, Needle Seat & Clip Assy. Alternator (Optional) Screw, 8-18 x 1-1/8" (3 required)(Opt.) Connector, A.C. Lighting (Optional) Connector, D.C. Charging (Optional) Tube, Centering (Optional) Alternator Shaft (Optional) Carburetor (Incl. 85) (Refer to Division 5, Section A, Page 182 for breakdown)  |

| Ref # | Part Number | Qty De               | escription  |
|-------|-------------|----------------------|---|
| 251   | 611038      | an<br>pu<br>sh       | lagneto NOTE: The complete magneto is not available as a ssembly. The magneto number is shown for reference urposes only. Order component parts individually, as nown in parts list. (Refer to Division 5, Section B, page 39 or breakdown)   |
| 252   | 590420A     |                      | ewind Starter (Refer to Division 5, Section C, page 25 for reakdown)  |
| 254   | 33328D      | mo<br>ad<br>bo<br>nu | tarter Motor Kit (110-120 volt) This 110-120 volt starter notor kit may have been added to this engine. It can be dded only if cylinder hasdrilled and tapped starter mounting osses and a ring gear flywheel (see#255). Refer to service umber stamped on end cap of motor or on decal for entificat |
| 255   | 30811A      | 11                   | lywheel (Ring gear flywheel requiredon engines using 10-120 volt starter motor kits listed above) (Used on Std. point ignition before 1982)   |
| 255   | 611042      | 11                   | lywheel (Ring gear flywheel requiredon engines using<br>10-120 volt starter motor kits listed above) (Used on Std.<br>pint ignition 1982 or later)  |
| 255   | 611085      | us                   | lywheel (Minimum ring gear flywheel required on engines sing 110-120 volt starter motor kits listed above) (Used on blid state external ignition)   |
| 256   | 33235A      | Ga                   | asket Set (Incl. items marked*)   |