

| Ref # | Part Number Qt | y Description |
|---|----------------|--|
| | 34919A | Cylinder (Incl. 2,3 & 4) (2-5/8" Bore) |
| | 27652 | Pin, Dowel |
| | | • |
| | 27642 | Pipe plug, 1/4-18 |
| | 32630 | Seal, Oil |
| 5 | 29536 | Blower Housing Baffle (Without electric starter knock out) |
| | | (Use as required) |
| 5 | 35256A | Blower Housing Baffle (With electric starter knockout) (As |
| · | 33-337 | req.)(point ign.) |
| | | |
| | 650561 | Screw, 1/4-20 x 5/8" |
| 7 | 29538 | Base, Engine mounting |
| 8 | 650542 | Screw, 5/16-18 x 3/4" |
| 9 | 35223 | Crankshaft |
| 10 | 29783 | Pin, Crankshaft gear (Used on early p rod.) |
| | 27884 | Gear, Crankshaft (Used on early production) This gear is |
| • | 2.661 | serviceable ONLY when it is pinned to the crankshaft. |
| | | · |
| | 34531 | Piston, Pin & Ring Set (Std.) (2-5/8" Bore) |
| | 34532 | Piston, Pin & Ring Set (.010" OS) |
| 13 | 34533 | Piston, Pin & Ring Set (.020" OS) |
| 13A | 33312B | Piston & Pin Ass'y. (Std.)(2-5/8")(In cl.14) |
| 13A | 33313B | Piston & Pin Ass'y. (.010" OS) (Incl. 14) |
| | 33314B | Piston & Pin Ass'y. (.020" OS) (Incl. 14) |
| | 27888 | Ring, Piston pin retaining |
| | 34854 | Ring Set (Std.) (2-5/8" Bore) |
| | 34855 | Ring Set (July OS) |
| | 34856 | Ring Set (.020" OS) |
| | | |
| | 31380C | Rod Assy., Connecting (Incl. 17) |
| | 650662C | Bolt, Connecting rod (Incl. 2 pieces) |
| | 34034 | Lifter, Valve |
| | 30622A | Extension, Blower housing |
| | 650128 | Screw, 10-24 x 1/2" |
| | 650561 | Screw, 1/4-20 x 5/8" (Use as required) |
| 22 | 30063 | Screw, 1/4-20 x 1/2" (Use as required) |
| 23 | 30684 | Gasket Cylinder Cover |
| 24 | 31451A | Cylinder Cover (Incl.26, 34, 127A, 12 9 & 130) |
| 26 | 28460 | Seal, Oil |
| 27 | 650488 | Screw, 1/4-20 x 1-1/4" |
| | 650493 | Screw, 1/4-20 x 1-3/4" |
| | 30699C | Rod Assy., Governor (Incl. 30 & 31) |
| | 30700 | Yoke, Governor |
| | 650494 | Screw, 6-40 x 5/16" |
| | 29642 | Ring, Retaining |
| | 31845 | Shaft, Mechanical governor |
| | 30588A | Spool, Governor |
| | 35479 | Washer, Flat |
| | 29193 | |
| | | Ring, Retaining |
| | 30591 | Gear Assy., Governor |
| | 31843A | Bracket, Governor gear |
| | 650836 | Screw, 10-24 x 1/2" |
| | 32783 | Intake Valve (Std.) |
| | 32784 | Intake Valve (1/32" OS) |
| | 27878A | Exhaust Valve (Std.) |
| 42 | 27880A | Exhaust Valve (1/32" OS) |
| 43 | 27882 | Cap, Upper valve spring |
| | 27881 | Spring, valve |
| | 32581 | Cap, Lower valve spring |
| | 650814 | Screw, 10-24 x 1" |
| | | · , · · · · · |

| | | Description |
|-----|---------|---|
| | 35187 | Wire, Ground |
| | 32589 | Key, Flywheel |
| | 28938C | Gasket, Cylinder head |
| | 30938A | Head, Cylinder |
| | 33636 | Resistor Spark Plug (RJ-8C) |
| 54 | 610118 | Cover, Spark plug (Use as required) |
| | 30939A | Cover Assy., Cylinder head |
| | 650691 | Washer, Flat (Use as required) |
| | 650690 | Washer, Belleville (Use as required) |
| | 650697A | Screw, 5/16-18 x 2-1/2" (Use as requi red) |
| | 650694A | Screw, 5/16-18 x 2" (Use as required) |
| | 650695A | Screw, 5/16-18 x 2-1/4" (Use as requi red) |
| | 30322 | Locknut, 8-32 |
| | 29916 | Clamp, Governor lever (Use as require d) |
| | 33454 | Lever Assy., Governor |
| | 29918 | Washer, Lock, No. 8 E.T. |
| | 650548 | Screw, 8-32 x 5/16" |
| | 29216 | Locknut, 10-32 |
| | 29826 | Screw, 10-32 x 3/4" |
| | 34661 | Link, Governor |
| | 34662 | Link, Throttle |
| | 34677 | Control Bracket (Incl. 68, 69, 72 & 1 38) |
| | 610973 | Terminal Assy. (Use as required) |
| | 27896A | Gasket, Valve chamber cover |
| | 28423 | Breather Assy., Valve |
| | 28424 | Element, Breather |
| | 28425 | Cover, Valve spring box |
| | 650128 | Screw, 10-24 x 1/2" |
| | 35350 | Tube Breather |
| | 27915A | * Gasket, Intake pipe to cylinder |
| | 34712 | Flange, Carburetor (Incl. 86A) |
| | 30196 | Screw, 5/16-18 x 3/4" |
| | 31688A | * Gasket, Carburetor |
| | 650517 | Screw, 1/4-20 x 13/16" |
| | 27272A | * Air Cleaner Gasket (Use as required) |
| | 30767 | Spacer, Cleaner (Use as required) |
| 94A | 34819 | Elbow Assy., Air cleaner (Incl. 90,91,92,93,94,96) (Use in |
| | | 730561 assembly only) |
| 101 | 34158 | Bracket, Fuel tank |
| | 650665 | Screw, 1/4-14 x 7/8" |
| | 34159 | Plate, Fuel tank mounting |
| | 34186A | Fuel Tank (Incl. 105 & 107) NOTE: These tanks were built |
| | 3113371 | with different size fuel inlet openings. Tanks with the 1-3/16" |
| | | I.D. opening use fuel cap 33032 or 34210. Tanks with the |
| | | 1-1/2" I.D. opening use fuel cap 35355. |
| | | |
| | 410144B | Fuel Cap (White Plastic)(Std.)(As req uired) |
| 105 | 33032 | Fuel Cap (Red Plastic) (Spurt resistant, Low profile) (Use as |
| | | required) |
| 105 | 34210 | Fuel Cap (Red Plastic) (Spurt resistant, High profile) (Use as |
| | | required) |
| | 05055 | • , |
| | 35355 | Fuel Cap (Red plastic) (Use as requir ed) |
| | 29774 | Fuel Line (Braided, 8 1/4") (Use as r equired) |
| | 30962 | Fuel Line (Braided, 32") (Use as required) |
| | 26460 | Clamp, Fuel line (Use as required) |
| | 32158E | Blower Housing (For electric starter) |
| 109 | 29747B | Screw, 5/16-24 x 21/32" |
| | | |

| Ref # | Part Number Qty | Description |
|-------|-----------------|---|
| 110 | 27930A | * Gasket, Exhaust flange |
| 111D | 33714 | Opt.Spark Arrest Muf.(Incl.112,143,14 4,144A) |
| 111 | 35275 | Muffler |
| 111E | 34390 | Deflector, Exhaust (Optional) |
| 111C | 391026 | Opt.Spark Arrest Muf.(Incl.143,143A,1 43B) |
| 112 | 30196 | Screw, 5/16-18 x 3/4" |
| | 26073 | Washer, Flat |
| | 650694A | Screw, 5/16 - 18 x 2" |
| | 32125 | Cup, Starter |
| | 35009 | Screen, Starter cup |
| | 650815 | Washer, Belleville |
| | 8116 | Nut, Hex |
| | 29716 | Screw, 1/4-28 x 7/16" |
| | 31691 | Bracket, Air cleaner |
| | 28820 | Screw, 10-32 x 1/2" |
| | 30727 | · |
| | | Element, Air cleaner |
| | 31715 | Body, Air cleaner |
| | 650152 | Screw, 8-32 x 3/8" |
| | 31855 | Retainer, Bearing |
| | 31793 | Bearing, Ball |
| | 31792 | Washer, Thrust |
| | 650778 | Washer, Lock |
| | 650580 | Nut, Lock |
| | 29443 | Clip, Ground wire |
| | 32410 | Knob, Speed control |
| | 34663 | Spring, Speed control |
| | 650821 | Screw, 10-32 x 1/2" |
| | 33171 | Screen, Muffler (Use as required) |
| 143 | 650578 | Screw, 8-18 x 3/8" (Use as required) |
| 143B | 33185 | Cover & tube, Muffler (Use as require d) |
| 144 | 33700 | Cover & Tube, Muffler (Use as require d) |
| 144A | 33323 | Screen, Muffler (Use as required) |
| 145 | 31297 | Dipstick (Incl. 146A) |
| 146A | 29673 | * Gasket, Oil fill |
| 167 | 34174 | Deflector, Exhaust |
| 168 | 650665 | Screw, 1/4-15 x 7/8" |
| 201A | 730130 | Muffler Adapter Kit (Incl.110,112)(As req.) |
| 201B | 730561 | Air Cleaner Kit |
| | | (Incl.74,79,80,87,88,89,90,91,92,94,95,96,97,99,100 & 230C) |
| | | (Used only on engine with an externally vented fully |
| | | adjustable carburetor) |
| 004 | 700404 | Air Olasson Apale (Dad Dak Viral 07 400 404 400 400 404 0 |
| 201 | 730164 | Air Cleaner Ass'y. (Red Poly)(Incl.87,120,121,122,123,124 & |
| | | 230)(As req.) |
| 201 | 730164 | Air Cleaner Kit, Mini bike (Incl.87,120,121,122,123 & 124) |
| | | (Use as required) |
| | | , |
| | 611084 | Flywheel |
| | 650872 | Stud, Solid State mounting |
| | 34443A | Solid State Assy. (Incl. 54) |
| | 34144 | Decal, Control |
| | 34346 | Decal, Instruction |
| | 30547A | Breaker Assy (Used on Std. Point igni tion) |
| | 631021 | Inlet, Needle Seat & Clip Assy. |
| 240 | 611077 | Alternator (Optional) |
| 241 | 650868 | Screw, 8-18 x 1-1/8" (3 required)(Opt .) |
| 242 | 611078 | Connector, A.C. Lighting (Optional) |
| 242 | 611079 | Connector, D.C. Charging (Optional) |
| | | |

| Ref # | Part Number | Qty | Description |
|-------|------------------|-----|---|
| | 590610 590613 | | Tube, Centering (Optional) Alternator Shaft (Optional) |
| | 632230 | | Carburetor (Incl. 85) (Refer to Division 5, Section A, Page 182 for breakdown) |
| 252 | 590420A | | Rewind Starter (Refer to Division 5, Section C, page 25 for breakdown) |
| 254 | 33328D | | Starter Motor Kit (110-120 volt) This 110-120 volt starter motor kit may have been added to this engine. It can be added only if cylinder hasdrilled and tapped starter mounting bosses and a ring gear flywheel (see#255). Refer to service number stamped on end cap of motor or on decal for identificat |
| 255 | 30811A | | Flywheel (Ring gear flywheel requiredon engines using 110-120 volt starter motor kits listed above) (Used on Std. point ignition before 1982) |
| 255 | 611042 | | Flywheel (Ring gear flywheel requiredon engines using 110-120 volt starter motor kits listed above) (Used on Std. point ignition 1982 or later) |
| 255 | 611085 | | Flywheel (Minimum ring gear flywheel required on engines using 110-120 volt starter motor kits listed above) (Used on solid state external ignition) |
| 256 | 33235A | | Gasket Set (Incl. items marked*) |