
H70-130216H Engine Parts List #1




| | | • | |
|-----|------------------|-----|--|
| | Part Number | Qty | |
| 1 | 32586C | | Cylinder (Incl. 2, 3, 4 & 76) (2-3/4" Bore) |
| | 27652 | | Pin, Dowel |
| | 27642 | | Plug, Oil drain |
| | 32630 | | Seal, Oil |
| | 32783 | | Intake Valve (Std.) (Incl. 9) |
| | 32784 | | Intake Valve (1/32" OS) (Incl. 9) |
| | 27878A | | Exhaust Valve (Std.) (Incl. 9) |
| | 27880A | | Exhaust Valve (1/32" OS) (Incl. 9) |
| | 20810 | | Pin, Valve spring retainer (Use as re quired) |
| | 27882 | | Cap, Upper valve spring |
| | 27881 | | Spring, Valve |
| | 27881 | | Spring, Valve |
| | 32581 | | Cap, Lower valve spring |
| | 32581 | | Cap, Lower valve spring |
| IUA | 32590 | | Plate, Lock & Oil dipper (This plate may be replaced by |
| | | | 34242 oil dipper but 650662C screw must be used.) |
| 10 | 34242 | | Dipper, Oil |
| 11 | 34894 | | Crankshaft (Incl. 12 & 13) |
| | 29783 | | Crankshaft Gear Pin (Early production) |
| 13 | 27884 | | Gear, Crankshaft (Used in early production) This gear is |
| | | | servicable onlywhen it is pinned to the crankshaft. |
| 14 | 34517 | | Piston, Pin & Ring Set (Std.) (2-3/4" Bore) |
| | 34518 | | Piston, Pin & Ring Set (.010" OS) |
| | 34519 | | Piston, Pin & Ring Set (.020" OS) |
| | 32592B | | Piston & Pin Ass'y. (Std.)(2-3/4")(In cl.16) |
| | 32593B | | Piston & Pin Ass'y. (.010" OS) (Incl. 16) |
| | 32594B | | Piston & Pin Ass'y. (.020" OS) (Incl. 16) |
| | 32595 | | Ring Set (Std.) (2-3/4" Bore) |
| | 32596 | | Ring Set (.010" OS) |
| 15 | 32597 | | Ring Set (.020" OS) |
| 16 | 27888 | | Ring, Piston pin retaining |
| 17 | 32591C | | Rod Assy., Connecting (Incl. 10 & 18) |
| 18 | 650662C | | Screw, Connecting rod (2 each) |
| 19 | 30968 | | Nipple, Oil drain |
| 20 | 30969 | | Cap, Oil drain |
| 21 | 32115 | | Camshaft (MCR) |
| 22 | 34034 | | Lifter, Valve |
| | 31303B | | Cover, Cylinder (Incl. 24, 106 & 279) |
| | 31546 | | Bushing, Crankshaft (Use as required) |
| | 28427 | | Seal, Oil |
| | 33893A | | Tube, Oil filler |
| | 34011A | | Dipstick, Oil (Incl. 30) |
| | 30684 | | * Gasket, Cylinder cover |
| | 650488 | | Screw, 1/4-20 x 1-1/4" |
| | 33590 | | "O" Ring |
| | 650489 | | Screw, 1/4-20 x 5/8" |
| | 32631A | | * Gasket, Cylinder head |
| | 30938A | | Head, Cylinder |
| | 27793 | | Clip, Conduit (Use as required) |
| | 28942 | | Screw, 10-32 x 3/8" (Use as required) |
| | 650697A | | Screw, 5/16-18 x 2-1/2" (Use as required) |
| | 650695A | | Screw, 5/16-18 x 2-1/4" (Use as required) |
| | 650694A 33636 | | Screw, 5/16-18 x 2" (Use as required) |
| | 33636 34251 | | Resistor Spark Plug (RJ-8C) |
| | 34251 27896A | | Resistor Spark Plug * Gasket, Breather cover |
| | 28423 | | Body, Breather |
| 39 | | | |

| | | Description |
|------|------------------|---|
| 40 | 28424 | Element, Breather |
| 41 | 28425 | Cover, Valve spring |
| 42 | 26073 | Washer (Use as required) |
| 42 | 650691 | Washer, Flat (Use as required) |
| | 650690 | Washer, Belleville (Use as required) |
| | 650128 | Screw, 10-24 x 1/2" |
| | 27915A | * Gasket, Intake |
| | 34712 | Flange Carburetor |
| | 30196 | Screw, 5/16-18 x 3/4" |
| | 29716 | Screw, 1/4-28 x 7/16" |
| | 650548 | Screw, 8-32 x 5/16" |
| | | • |
| | 33454 | Lever Assy., Governor |
| | 34662 | Link, Throttle |
| | 29216 | Nut, Lock, 10-32 |
| | 29826 | Screw, 10-32 x 3/4" |
| | 29642 | Ring, Retaining |
| | 30699C | Rod Assy., Governor (Incl. 64 & 65) |
| 63 | 30699B | Governor Rod Ass'y. (This one-piece governor rodis no longer |
| | | used. It is replaced by 30699C ass'y.,Ref. no. 63A) |
| C.4 | 20700 | Vales Covernor |
| | 30700 | Yoke, Governor |
| | 650494 | Screw, 6-40 x 5/16" |
| | 29918 | Lockwasher, #8 E.T. |
| | 35350 | Tube, Breather |
| | 29747B | Screw, 5/16-24 x 21/32" |
| | 35260 | Blower Housing (For electric starter) |
| 71 | 650815 | Washer, Belleville |
| | 8116 | Nut, Hex |
| 73 | 29536 | Blower Housing Baffle (without electric starter knock-out) |
| | | (Use as required) |
| 72 | 35256A | Blower Housing Baffle (with electric starter knock-out) (Use |
| 15 | 50250A | as required) (Point Ignition) |
| | | |
| 74 | 650561 | Screw, 1/4-20 x 5/8" |
| 75 | 31688A | * Gasket, Carburetor |
| 80A | 650517 | Screw, 1/4-20 x 27/32" |
| 82A | 730164 | Air Cleaner Ass'y. (Incl. 60, 83, 87, 88, 89, 90A & 331B) |
| | | (Use as required) |
| 07 | 34240 | Ground Wire |
| | 29538 | |
| | | Base, Engine mounting |
| | 32401 | Muffler |
| | 31845 | Shaft, Mechanical governor |
| | 30591 | Gear Assy., Governor (Incl. 109) |
| | 30588A | Spool, Governor |
| | 30590A | Washer, Flat |
| | 29193 | Ring, Retaining |
| 111C | 34158 | Bracket, Fuel tank |
| 113 | 650561 | Screw, 1/4-20 x 5/8" |
| 114 | 34186A | Fuel Tank (Incl. 115 & 266) NOTE: These tanks were built |
| | | with different size fuel inlet openings. Tanks with the 1-3/16" |
| | | I.D. opening use fuel cap 33032 or 34210. Tanks with the |
| | | 1-1/2" I.D. opening use fuel cap 35355 or 35650. |
| | | |
| | ····· | |
| | 410144B | Fuel Cap (White Plastic)(Std)(As requ ired) |
| | 410144B 33032 | |

| | | ty Description |
|-----|---------|--|
| 115 | 34210 | Fuel Cap (Red Plastic) (Spurt resistant, High profile) (Use as |
| | | required) |
| 115 | 35355 | Fuel Cap (Use as required) |
| | 34159 | Plate, Fuel tank mounting |
| | 32961 | Valve, Shut-off |
| | 29774 | Fuel Line (Braided 8-1/4" 21 cm)(Use as req.) |
| | 30705 | Fuel Line (Braided 16") (41 cm) (Use as req.) |
| | 30962 | Fuel Line (Braided 32") (81 cm) (Use as req.) |
| | 650128 | Screw, $10-24 \times 1/2^{"}$ (Use as required) |
| | 30622A | |
| | | Extension, Blower housing |
| | 650542 | Screw, 5/16-18 x 3/4" |
| | 27930A | Gasket, Exhaust |
| | 30196 | Screw, 5/16-18 x 3/4" |
| | 26073 | Washer (Use as required) |
| | 650694A | Screw, 5/16-18 x 2" (Use as required) |
| | 32589 | Key, Flywheel |
| | 31843A | Bracket, Governor gear |
| | 650836 | Screw, 10-24 x 1/2" |
| 133 | 650493 | Screw, 1/4-20 x 1-3/4" |
| 149 | 30747 | Clip, Shorting |
| 151 | 650665 | Screw, 1/4-15 x 7/8" |
| 193 | 610118 | Cover, Spark plug (Use as required) |
| 205 | 650561 | Screw, 1/4-20 x 5/8" (Use as required) |
| | 30939A | Cover, Cylinder head |
| | 34814 | Primer Assy. |
| | 32180C | Line, Primer |
| | 34126 | Bracket, Grommet mounting |
| | 650760 | Screw, 8-32 x 3/8" |
| | 28545 | Grommet |
| | 32125 | Cup, Starter |
| | 35009 | • |
| | | Screen, Starter cup |
| | 26460 | Clamp, Fuel line |
| | 31461 | Bushing, Crankshaft (Use as required) |
| | 33876 | Gasket, Stator |
| | 610973 | Terminal Ass'y. (As req. on late prod uction) |
| | 27275 | Clip, Hi-tension wire (Use as require d) |
| | 34246 | Clip, Ground wire (Use as required) |
| | 34346 | Decal, Instruction |
| 331 | 550223 | Decal, Name |
| 332 | 30547A | Contact Assy., Breaker |
| 333 | 30548B | Condenser |
| 334 | 631021 | Inlet Needle, Seat & Clip Assy. |
| 336 | 631920 | Carburetor (Incl. 75) (Refer to Division 5, Section A, page 13 |
| | | for breakdown) |
| 207 | C14040 | , |
| 337 | 611043 | Magneto (w/ring gear) NOTE: The complete magneto is not |
| | | available as an assembly. The magneto number is shown for |
| | | reference purposes only. Order component parts |
| | | individually, as show in parts list. (Refer to Division 3, |
| | | Section B, page 39 for breakdown) |
| 228 | 590473 | Rewind Starter (Refer to Division 5, Section C, page 29 for |
| 550 | 017000 | breakdown) |
| | | DICANUOWIII |
| | | |



| | Part Number Qt | |
|-----|----------------|---|
| | 650489 | Screw, 1/4-20 x 5/8" |
| | 27793 | Clip, Conduit (Use as required) |
| | 28942 | Screw, 10-32 x 3/8" (Use as required) |
| | 650128 | Screw, 10-24 x 1/2" |
| | 29716 | Screw, 1/4-28 x 7/16" |
| | 34662 | Link, Throttle |
| | 650815 | Washer, Belleville |
| | 8116 | Nut, Hex |
| | 33013 | Cover, Bubble |
| | 650760 | Screw, 8-32 x 3/8" |
| | 34663 | Spring, Speed control |
| | 650821 | Screw, 10-32 x 1/2" |
| | 34661 | Link, Governor |
| | 610118 | Cover, Spark plug (Use as required) |
| | 35438 | Knob, Control |
| | 32410 | Knob, Speed control |
| | 32180C | Line, Primer |
| | 30826 | Spring, Extension |
| | 650257 | Screw, 8-32 x 5/16" |
| | 34672 | Cover, Carburetor |
| | 32398 | Bracket, Choke |
| | 28820 | Screw, 10-32 x 1/2" |
| | 650760 | Screw, 8-32 x 3/8" |
| | 650765 | Screw, 10-32 x 1/2" |
| | 650764 | Nut, "U" Type (Use as required) |
| | 34677 | Control Bracket (Incl. 98, 99, 180A & 274) |
| | 610973 | Terminal Ass'y. (As req. on late prod uction) |
| | 34127 | Guard Starter |
| | 32576 | Seal, Snow guard |
| | 550223 | Decal, Name |
| | 34414 | Decal, Warning |
| | 34680 | Decal, Instruction |
| | 34416 | Decal, Choke |
| | 34144 | Decal, Primer |
| 338 | 590473 | Rewind Starter (Refer to Division 5, Section C, page 29 for |
| | | breakdown) |
| 340 | 33328D | Starter Motor Kit (110-120 Volt) This 110-120 volt starter motor kit may have been added to this engine. It can be added only if cylinder hasdrilled and tapped starter mounting bosses and a ring gear flywheel (see#342). Refer to service number stamped on end cap of motor, or on decal, for identifica |
| 342 | 30811A | Flywheel (Ring gear flywheel requiredon engines using 110-120 volt starter kits listed above) |
| 342 | 611042 | Flywheel (Used on Type letters H and above) (Std. Point ignition) (Ring gear flywheel required on engines using 110-120 volt starter kits listed above) |
| 342 | 611085 | Flywheel (Minimum ring gear flywheel required on engines using 110-120 volt starter kits listed above) (Use withSolid State ignition) |



| Ref # | Part Number Q | ty Description |
|-------|-------------------|--|
| 27 | 27513 | Lockwasher, 1/4" (Use as required) |
| 36 | 650697A | Screw, 5/16-18 x 2-1/2" (Use as requi red) |
| 36 | 650695A | Screw, 5/16-18 x 2-1/4" (Use as required) |
| 36 | 650694A | Screw, 5/16-18 x 2" (Use as required) |
| 38 | 27896A | * Gasket, Breather cover |
| 42 | 26073 | Washer (Use as required) |
| 42 | 650691 | Washer, Flat (Use as required) |
| 50 | 650548 | Screw, 8-32 x 5/16" |
| | 30319 | Rivet, Split (Used in early productio n) |
| | 33454 | Lever Assy., Governor |
| | 730130 | Exh.Adap.Kit (Incl. 58 & 125) (Use as req.) |
| | 30196 | Screw, 5/16-18 x 3/4" (Use as require d) |
| | 29216 | Nut, Lock, 10-32 |
| | 29826 | Screw, 10-32 x 3/4" |
| | 29918 | Lockwasher, #8 E.T. |
| | 730561 | Air cleaner kit (Incl. 38, 67A, 83, 84B, 85,89B, 89C, 90A, 91, |
| | | 91A, 91B, 91C, 91D, 245 & 331B) (Use only on engines with |
| | | an externally vented fully adjustable carburetor) |
| | 700407 | |
| 82 | 730127 | Air Cleaner Ass'y. (Incl. 60, 83, 87, 88, 89A, 90, 238 & |
| | | 331B) (Use as required) |
| 84D | 34819 | Air Cleaner Elbow (Incl. 84B, 86A, 91, 91A, 91B & 91C) (Use |
| | | in 730561 assembly only) NOTE: 130010 thru 10C & 11 |
| | | used in early production only. |
| 1005 | 391026 | |
| | | Opt. Spark Arrest Muffler (Incl.196,1 97,199) |
| | 650561 | Screw, 1/4-20 x 5/8" Evol Line (Proided 8 1/4" 21 cm)(Line co rog.) |
| | 29774 | Fuel Line (Braided 8-1/4" 21 cm)(Use as req.) |
| | 30705 | Fuel Line (Braided 16") (41 cm) (Use as req.) |
| | 30962 | Fuel Line (Braided 32") (81 cm) (Use as req.) |
| | 27930A | Gasket, Exhaust |
| | 30196 | Screw, 5/16-18 x 3/4" |
| | 650694A 650548 | Screw, 5/16-18 x 2" (Use as required) |
| | 34067 | Screw, 8-32 x 5/16" (Early production) |
| | | Wire Assy., Alternator adapter (4-1/4 ") |
| | 34069 | Wire Assy., Alternator adapter (6-3/4 ") |
| | 30322 | Nut & Lockwasher (Early Prod. Only) |
| | 29916 | Clamp, Governor lever (Early Prod. On ly) |
| | 31288 | Exh. Adaptor Kit (Incl.125,203,204) (As req.) |
| | 650697A | Screw, 5/16-18 x 2-1/2" (Use as required) |
| | 6021A | Screw, 5/16-18 x 1-1/2" (Use as required) |
| | 650760 | Screw, 8-32 x 3/8" |
| | 28545 | Grommet |
| 266 | 26460 | Clamp, Fuel line |