




| | 5 | <u> </u> |
|-----|----------|---|
| | | / Description |
| | 35371 | Cylinder (CI liner)(3-5/16")(Incl.2,2 0 & 72) |
| | 27652 | Pin, Dowel |
| | 30699C | Rod Assy., Governor (Incl. 15A & 15B) |
| | 650494 | Screw, 6-40 x 5/16" |
| 15A | 30700 | Yoke, Governor |
| 16 | 33454 | Governor Lever Assy. |
| 17 | 29916 | Clamp, Governor lever |
| 18 | 650548 | Screw, 8-32 x 5/16" |
| 20 | 35319 | Seal, Oil |
| | 35256A | Blower Housing Baffle (With electric starter knockout) (Use |
| 20 | 00200/ t | as required) |
| | | as required) |
| 25 | 35326 | Baffle, Blower housing |
| 25 | 29536 | Blower Housing Baffle (Without electric starter knockout) |
| | | (Use as required) |
| 00 | 050504 | Corour 4/4 20 v E/0!! |
| | 650561 | Screw, 1/4-20 x 5/8" |
| | 35372A | Crankshaft (Incl. 108 & 109) |
| | 29826 | Screw, 10-32 x 3/4" |
| | 29918 | Lockwasher, #8 E.T. |
| 37 | 29216 | Locknut, 10-32 |
| 37A | 30322 | Nut & Lockwasher, 8-32 |
| 38 | 29642 | Ring, Retaining |
| 40 | 34860A | Piston, Pin & Ring Set (Std.)(3-5/16") |
| 40 | 34861A | Piston, Pin & Ring Set (.010" OS) |
| | 34862A | Piston, Pin & Ring Set (.020" OS) |
| | 34863 | Piston & Pin Ass'y. (Std.)(3-5/16")(I ncl.43) |
| | 34864 | Piston & Pin Ass'y. (.010" OS) (Incl. 43) |
| | 34865 | Piston & Pin Ass'y. (.020" OS) (Incl. 43) |
| | | |
| | 34866A | Ring Set (Std.) (3-5/16" Bore) |
| | 34867A | Ring Set (.010" OS) |
| | 34868A | Ring Set (.020" OS) |
| | 27888 | Ring, Piston Pin retaining |
| | 35373A | Rod Assy., Connecting (Incl. 46, 47 & 49) |
| | 650908 | Bolt, Connecting rod |
| | 650882 | Connecting Rod Bolt (2 pcs. on early Specs.) |
| 48 | 34034 | Lifter, Valve |
| 49 | 35374 | Dipper, Oil |
| 50 | 35375 | Camshaft (MCR) |
| | 33273A | Extension, Blower housing |
| | 650128 | Screw, 10-24 x 1/2" |
| | 35262 | * Gasket, Flange |
| | 35376 | Cover, Cylinder (Incl. 71, 75 & 80) |
| | 35377 | Bushing, Crankshaft |
| | 27642 | Plug, Oil drain |
| | 35319 | Seal, Oil |
| | | · |
| | 31845 | Shaft, Mechanical governor |
| | 30590A | Washer, Flat |
| | 35378 | Gear Assy., Governor (Incl. 81) |
| | 30588A | Spool, Governor |
| | 29193 | Ring, Retaining |
| | 650833 | Screw, 1/4-20 x 1-3/16 (Use as requir ed) |
| 87 | 650832 | Screw, 1/4-20 x 1-11/16" (Use as requ ired) |
| 89 | 32589 | Key, Flywheel |
| | 611090 | Flywheel |
| | 650880 | Washer, Lock |
| | 650881 | Nut, 5/8-18 |
| | 35135 | Solid State Assy. |
| | 650872 | Stud, Solid state mounting |
| 102 | 000012 | Stad, John State Mounting |


| | 5 (1) | B 14 |
|------|---------|---|
| | | Description T 45 40 04 4" |
| | 650814 | Screw, Torx T-15, 10-24 x 1" |
| 108 | 29783 | Pin, Crankshaft gear (Only serviceable when gear is pinned |
| | | to crank.) |
| 109 | 33245 | Gear, Crankshaft |
| | 34923A | * Gasket, Cylinder head |
| | 34030A | • |
| | | Head, Cylinder |
| | 27878A | Exhaust Valve (Std.) (Incl. 151) |
| | 27880A | Exhaust Valve (1/32" OS) (Incl. 151) |
| | 34035 | Intake Valve (Std.) (Incl. 151) |
| | 34036 | Intake Valve (1/32" OS) (Incl. 151) |
| | 650691 | Washer (Do not use with No. 6021A scr ew.) |
| 128 | 650690 | Washer, Belleville (Use as required) |
| 129 | 650727 | Screw, 5/16-18 x 1-3/4 (Use as requir ed) |
| 130 | 6021A | Screw, 5/16-18 x 1-1/2" (Use as required, but do notuse No. |
| | | 650691 washer.) |
| 400 | 0=0=44 | , |
| 130 | 650711 | Screw, 5/16-18 x 1-5/8 " (Use as required) (Can use 6021A |
| | | but discard 650691 washer.) |
| 130 | 650694A | Screw, 5/16-18 x 2" (Use as required) |
| | 650713 | Screw, 5/16-18 x 5/8" |
| | | · |
| | 650737 | Screw, 1/4-20 x 1/2" (Use as required) |
| | 650738 | Screw, 1/4-20 x 5/8 (Use as required) |
| | 650890 | Washer, Internal Lock |
| | 30747 | Clip, Spark plug shorting |
| 135 | 33636 | Resistor Spark Plug |
| 139 | 33369 | Bracket, Governor gear |
| 140 | 650836 | Screw, 10-24 x 1/2" |
| | 35862 | Seal Assy., Intake valve |
| | 27881 | Spring, Valve |
| | 32581 | Cap, Lower valve spring |
| | 27896A | * Gasket, Breather |
| | 28423 | · |
| | | Body, Breather |
| | 28424 | Element, Breather |
| | 28425 | Cover, Breather |
| | 35350 | Tube, Breather |
| | 650128 | Screw, 10-24 x 1/2" |
| | 29752 | Nut & Lockwasher, 1/4-28 |
| 182 | 30088A | Screw, 1/4-28 x 1" |
| 184 | 33263 | * Gasket, Carburetor |
| 185 | 34707 | Pipe, Intake |
| 186 | 34661 | Link, Governor lever |
| 200 | 34664 | Control Bracket (Incl.19,203, 204, 20 6 & 209) |
| | 31342 | Spring, Compression |
| | 650549 | Screw, 5-40 x 7/16" |
| | 33878 | Link, Governor lever-to-throttle |
| | 650821 | Screw, 10-32 x 1/2" |
| | 27793 | · |
| | 21133 | Clip, Conduit |
| 222A | CE0270 | Pop Rivet (Can be purchased locally) |
| | 650378 | Screw, Torx T-30, 5/16-18 x 1-1/8" |
| | 27915A | * Gasket, Intake pipe |
| | 33269A | Cover, Air cleaner |
| | 33375D | Blower Housing (For electric starter) |
| 261 | 650788 | Screw, 5/16-18 x 3/4" |
| 262 | 29747B | Screw, 5/16-24 x 21/32" |
| | 33272B | Cover, Cylinder head |
| | 33280A | Muffler |
| | 31588 | Plate, Muffler locking |
| 210 | 0.1000 | i ato, mainor rooming |


| Ref # | Part Number 0 | Qty | Description |
|-------|--------------------|-----|---|
| 276 | 35741 | | Plate, Muffler locking |
| 277 | 650729 | | Screw, 5/16-18 x 3-3/16" (Use as requ ired) |
| 277 | 651002 | | Screw, 5/16-18 x 4-1/4" (Use as requi red) |
| 281 | 33013 | | Cover, Starter bubble |
| 282 | 650760 | | Screw, 8-32 x 7/16" |
| 285 | 35287 | | Cup, Starter |
| 286 | 35194 | | Screen, Starter |
| 287 | 29752 | | Nut, 1/4-28 |
| 290 | 29774 | | Fuel Line (Braided 8-1/4")(21cm)(As r equired) |
| 290 | 30962 | | Fuel Line (Braided 32")(80cm)(As required) |
| 291 | 30705 | | Fuel Line (Braided 16")(40cm)(As required) |
| 292 | 26460 | | Fuel Line Clamp (Use as required) |
| 298 | 650665 | | Screw, 1/4-15 x 7/8" |
| 300 | 34156A | | Fuel Tank (Incl. 292 & 301) NOTE: These tanks were |
| | | | builtwith different size fuel inlet openings. Tanks with the |
| | | | 1-3/16" I.D. opening use fuel cap 34210. Tanks with the |
| | | | 1-1/2" I.D. opening use fuel cap 35355. |
| 201 / | 440444D | | |
| 301A | 410144B | | Fuel Cap (White Plastic)(Standard) (Use as required) (1.5" |
| | | | I.D.) |
| 301A | 33032 | | Fuel Cap (Red Plastic) (Spurt Resistant, Low Profile) (Use as |
| | | | required) (1.5" I.D.) |
| 3∩1∆ | 34210 | | Fuel Cap (Red Plastic) (Spurt Resistant, High Profile) (Use |
| 30 IA | 0 1 210 | | as required) (1.5" I.D.) |
| | | | . , , , |
| | 35355 | | Fuel Cap (Red Plastic)(1.75" I.D.) |
| | 29673 | | * Gasket, Oil filler |
| | 31297 | | Dipstick (Incl. 307) |
| | 31291 | | Plug, Cover |
| | 34154 | | Plate, Upper fuel tank mtg. |
| | 34155 | | Bracket, Lower fuel tank mtg. |
| | 650561 | | Screw, 1/4-20 x 5/8" |
| | 34346 | | Decal, Instruction |
| | 35274 | | Decal, Instruction |
| | 34686 | | Decal, Name |
| | 631021 | | Inlet Needle, Seat & Clip Assy. |
| 380 | 632242 | | Carburetor (Incl. 184 & 379) (Refer to Division 5, Section A, |
| | | | page A4-4 for breakdown or Fiche 18B, Grid D-3) |
| 400 | 33279G | | * Gasket Set (Incl. items marked *) |
| | 730225 | | SAE 30 4-Cycle Engine Oil (Quart) |
| | 730226 | | SAE 5W30 4-Cycle Engine Oil (Quart) |
| | 35824 | | Muffler Optional |
| 722 | 00021 | | mailor Optional |






















| Ref # | Part Number | Qty | Description |
|-------|-------------|-----|---|
| 37A | 30322 | | Nut & Lockwasher, 8-32 |
| 129 | 650727 | | Screw, 5/16-18 x 1-3/4 (Use as requir ed) |
| 131A | 650713 | | Screw, 5/16-18 x 5/8" |
| 131 | 650737 | | Screw, 1/4-20 x 1/2" (Use as required) |
| 131 | 650738 | | Screw, 1/4-20 x 5/8 (Use as required) |
| 222A | | | Pop Rivet (Can be purchased locally) |
| 250B | 33269A | | Cover, Air cleaner |
| 274 | 35865 | | Gasket, Exhaust |
| 275 | 33280A | | Muffler |
| 277 | 650729 | | Screw, 5/16-18 x 3-3/16" (Use as requ ired) |
| 277 | 651002 | | Screw, 5/16-18 x 4-1/4" (Use as requi red) |
| 290 | 29774 | | Fuel Line (Braided 8-1/4")(21cm)(As r equired) |
| | 30962 | | Fuel Line (Braided 32")(80cm)(As required) |
| 292 | 26460 | | Fuel Line Clamp (Use as required) |
| 298 | 650665 | | Screw, 1/4-15 x 7/8" |
| 300 | 34156A | | Fuel Tank (Incl. 292 & 301) NOTE: These tanks were |
| | | | builtwith different size fuel inlet openings. Tanks with the |
| | | | 1-3/16" I.D. opening use fuel cap 34210. Tanks with the |
| | | | 1-1/2" I.D. opening use fuel cap 35355. |
| 301A | 410144B | | Fuel Cap (White Plastic)(Standard) (Use as required) (1.5" |
| | | | I.D.) |
| 004 A | 00000 | | · |
| 301A | 33032 | | Fuel Cap (Red Plastic) (Spurt Resistant, Low Profile) (Use as |
| | | | required) (1.5" I.D.) |
| 301A | 34210 | | Fuel Cap (Red Plastic) (Spurt Resistant, High Profile) (Use |
| | | | as required) (1.5" I.D.) |
| 301A | 35355 | | Fuel Cap (Red Plastic)(1.75" I.D.) |
| | 29673 | | * Gasket, Oil filler |
| | 31291 | | Plug, Cover |
| | 34155 | | Bracket, Lower fuel tank mtg. |
| | 650561 | | Screw, 1/4-20 x 5/8" |
| | 33323 | | Opt.Muffler Screen (Mini-Bike applica tion) |
| | 730130 | | Kit, Exhaust adapter (Incl. 274 & 277) |
| | 33700 | | Cover & Tube, Muffler (use as require d) |
| | 650578 | | Screw, 8-18 x 3/8" (use as required) |
| | 730226 | | SAE 5W30 4-Cycle Engine Oil (Quart) |
| | 35824 | | Muffler Optional |
| | | | 1 |



| Ref # | Part Number Qty | Description |
|-------|-----------------|---|
| 37A | 30322 | Nut & Lockwasher, 8-32 |
| 129 | 650727 | Screw, 5/16-18 x 1-3/4 (Use as requir ed) |
| 131 | 650737 | Screw, 1/4-20 x 1/2" (Use as required) |
| 131 | 650738 | Screw, 1/4-20 x 5/8 (Use as required) |
| | 650713 | Screw, 5/16-18 x 5/8" |
| | 730152 | Control Bracket (Incl.1158-1171)(As r eq.) |
| | 31342 | Spring, Compression |
| | 650549 | Screw, 5-40 x 7/16" |
| | 27793 | Clip, Conduit |
| 222A | 2.100 | Pop Rivet (Can be purchased locally) |
| | 730127 | Air Cleaner Ass'y. (Incl. 238, 239, 242, 246, 250) (Use as |
| | 7.55.12. | required) |
| 238 | 28820 | Screw, 10-32 x 1/2" |
| 239 | 27272A | * Gasket, Air cleaner |
| 241 | 33266 | Bracket, Air cleaner |
| 242 | 33267 | Bracket, Air cleaner |
| 245 | 33268 | Element, Air cleaner |
| | 33269A | Cover, Air cleaner |
| | 650513 | Nut, Wing 1/4-20 |
| | 29774 | Fuel Line (Braided 8-1/4")(21cm)(As r equired) |
| | 30962 | Fuel Line (Braided 32")(80cm)(As required) |
| | 30705 | Fuel Line (Braided 16")(40cm)(As required) |
| | 33715 | Impulse Fuel Pump NOTE: 34385 and 33715 (WIP)pumps |
| 200 | 607.10 | are replaced by 35813 and 35800 (WIP) pumps. The 33010 |
| | | (3000 series) repair kit is still available. The 35791 repair kit |
| | | is used with the 35813 and 35800 fuel pumps. |
| | | • • |
| 294 | 35791 | Fuel Pump Repair Kit NOTE: 34385 and 33715 (WIP)pumps |
| | | are replaced by 35813 and 35800 (WIP) pumps. The 33010 |
| | | (3000 series) repair kit is still available. The 35791 repair kit |
| | | is used with the 35813 and 35800 fuel pumps. |
| 301A | 410144B | Fuel Cap (White Plastic)(Standard) (Use as required) (1.5" |
| | | I.D.) |
| 301A | 33032 | Fuel Cap (Red Plastic) (Spurt Resistant, Low Profile) (Use as |
| | | required) (1.5" I.D.) |
| 301A | 34210 | Fuel Cap (Red Plastic) (Spurt Resistant, High Profile) (Use |
| | | as required) (1.5" I.D.) |
| 301A | 35355 | Fuel Cap (Red Plastic)(1.75" I.D.) |
| 303 | 32958 | Fitting, Fuel |
| | 29673 | * Gasket, Oil filler |
| | 31291 | Plug, Cover |
| | 34346 | Decal, Instruction |
| | 35274 | Decal, Instruction |
| | 730226 | SAE 5W30 4-Cycle Engine Oil (Quart) |
| | 35824 | Muffler Optional |
| | 30312 | Screw, 10-32 x 1/2" |
| | 28820 | Screw, 10-32 x 1/2" |
| | 27070 | Lockwasher |
| | 33816 | Hub & Screen Assy. |
| 1.00 | | |



| Ref # | Part Number | Otv | Description |
|-------------|-------------|-----|--|
| | 35371 | Qty | Cylinder (CI liner)(3-5/16")(Incl.2,2 0 & 72) |
| | 27652 | | Pin, Dowel |
| | 30322 | | Nut & Lockwasher, 8-32 |
| | 27642 | | Plug, Oil drain |
| | 611090 | | Flywheel |
| | 35135 | | Solid State Assy. |
| | 650872 | | Stud, Solid state mounting |
| | 650814 | | Screw, Torx T-15, 10-24 x 1" |
| | 650727 | | Screw, 5/16-18 x 1-3/4 (Use as requir ed) |
| | 650737 | | Screw, 1/4-20 x 1/2" (Use as required) |
| | 650738 | | Screw, 1/4-20 x 5/8 (Use as required) |
| | 650713 | | Screw, 5/16-18 x 5/8" |
| | 27896A | | * Gasket, Breather |
| | 28423 | | Body, Breather |
| | 28424 | | Element, Breather |
| | 28425 | | Cover, Breather |
| | 35350 | | Tube, Breather |
| | 650128 | | Screw, 10-24 x 1/2" |
| | 29752 | | Nut & Lockwasher, 1/4-28 |
| | 33878 | | Link, Governor lever-to-throttle |
| 207 222A | | | Pop Rivet (Can be purchased locally) |
| | 28820 | | Screw, 10-32 x 1/2" |
| | 27272A | | * Gasket, Air cleaner |
| | 33266 | | · |
| | 33267 | | Bracket, Air cleaner |
| | | | Bracket, Air cleaner |
| | 33268 | | Element, Air cleaner |
| | 33269A | | Cover, Air cleaner |
| | 650513 | | Nut, Wing 1/4-20 Muffler (Incl. 284 2844 & 416) (This appels arrestor |
| 2/30 | 391026 | | Muffler (Incl. 284, 284A & 416) (This spark arrester |
| | | | mufflercan be used on any model.) |
| 275 | 33280A | | Muffler |
| 276 | 31588 | | Plate, Muffler locking |
| 276 | 35741 | | Plate, Muffler locking |
| 277 | 650729 | | Screw, 5/16-18 x 3-3/16" (Use as requ ired) |
| 277 | 651002 | | Screw, 5/16-18 x 4-1/4" (Use as required) |
| 301A | 410144B | | Fuel Cap (White Plastic)(Standard) (Use as required) (1.5" |
| | | | I.D.) |
| 2014 | 22022 | | · |
| 30 IA | 33032 | | Fuel Cap (Red Plastic) (Spurt Resistant, Low Profile) (Use as |
| | | | required) (1.5" I.D.) |
| 301A | 34210 | | Fuel Cap (Red Plastic) (Spurt Resistant, High Profile) (Use |
| | | | as required) (1.5" I.D.) |
| 204.4 | 05055 | | First Care (Bard Blacks)/4.75" LD.) |
| | 35355 | | Fuel Cap (Red Plastic)(1.75" I.D.) |
| | 29673 | | * Gasket, Oil filler |
| | 33876 | | Gasket, Stator (Used only on Std. poi nt ign.) |
| | 31291 | | Plug, Cover |
| | 30547A | | Breaker Points (Use with Std. point i gn.) |
| 380 | 632242 | | Carburetor (Incl. 184 & 379) (Refer to Division 5, Section A, |
| | | | page A4-4 for breakdown or Fiche 18B, Grid D-3) |
| 421 | 730226 | | SAE 5W30 4-Cycle Engine Oil (Quart) |
| | 35824 | | Muffler Optional |
| | | | - I |