


| Ref # | Part Number Qty | Description |
|-------|-----------------|--|
| 1 | 34348B | Cylinder (Incl.2,20,72,72A) (3-1/8" B ore) |
| 2 | 27652 | Pin, Dowel |
| 3 | 650820 | Screw, 1/4-20 x 1/2" |
| 15B | 650494 | Screw, 6-40 x 5/16" |
| 15A | 30700 | Yoke, Governor |
| 15 | 30699C | Rod Assy., Governor (Incl. 15A & 15B) |
| 16 | 33454 | Governor Lever Assy. |
| 17 | 29916 | Clamp, Governor lever |
| 18 | 650548 | Screw, 8-32 x 5/16" |
| | 34663 | Spring, Speed control |
| | 32630 | Seal, Oil |
| | 35256A | Baffle, Blower housing |
| | 650561 | Screw, 1/4-20 x 5/8" |
| | 33719B | Crankshaft (Incl. 108 & 109) |
| | 29826 | Screw, 10-32 x 3/4" |
| | 29918 | Lockwasher, #8 E.T. |
| | 29216 | Nut & Lockwasher, 10-32 "Keps" |
| | 30322 | Locknut, Hex "Keps", 8-32 |
| | 29642 | Ring, Retaining |
| | 34552 | Piston, Pin & Ring Set (Std.) (3-1/8") |
| | 34553 | Piston, Pin & Ring Set (.010" OS) |
| | 34554 | Piston, Pin & Ring Set (.020" OS) |
| | 34329A | Piston & Pin Ass'y.(Std)(Incl.43)(3-1 /8") |
| | 34330A | Piston & Pin Ass'y. (.010" OS)(Incl. 43) |
| | 34331A | Piston & Pin Ass'y. (.020" OS)(Incl. 43) |
| | 34332 | Ring Set (Std.) (3-1/8" Bore) |
| | 34333 | Ring Set (.010" OS) |
| | 34334 | Ring Set (.020" OS) |
| | 27888 | Ring, Piston pin retaining |
| | 32591C | Rod Assy., Connecting (Incl. 49) |
| | 650662C | Bolt, Connecting rod (2 pieces) |
| | 34034 | Lifter, Valve |
| | 34242 | Dipper, Oil |
| | 34143 | Camshaft (MCR) |
| | 33273A | Extension, Blower housing |
| | 34126 | Bracket, Grommet mounting |
| | 650760 | Screw, 8-32 x 3/8" |
| | 28545 | Grommet, Plastic |
| | 650128 | Screw, 10-24 x 1/2" |
| 69 | 35262 | * Gasket, Cylinder cover |
| | 33367B | Cylinder Cover (Incl. 71, 75, 80, 311 & 312) |
| | 33368 | Bushing, Crankshaft |
| | 27642 | Plug, Oil drain |
| | 31950 | Seal, Oil |
| | 31845 | Shaft, Mechanical governor |
| | 30590A | Washer, Flat |
| | 30591 | Gear Assy., Governor (Incl. 81) |
| | 30588A | Spool, Governor |
| | 29193 | Ring, Retaining |
| | 650833 | Screw, 1/4-20 x 1-3/16" |
| | 650832 | Screw, 1/4-20 x 1-11/16" |
| | 32589 | Key, Flywheel |
| | 650815 | Washer, Belleville |
| | 8116 | Nut, Hex (1/2-20) |
| | 610118 | Cover, Spark plug (Use as required) |
| | 650516 | Screw, 1/4-20 x 1-1/8 |
| | 29783 | Pin, Crankshaft gear |
| | 33245 | Gear, Crankshaft |
| | | , |

| Ref # | Part Number Qty | Description |
|-------|-----------------|--|
| | 610609 | Ground Wire |
| | 34041A | * Gasket, Head |
| | 34030A | Head, Cylinder |
| | 27878A | Exhaust Valve (Std.) (Incl. 151) |
| | 27880A | Exhaust Valve (1/32" OS) (Incl. 151) |
| | 34035 | Intake Valve (Std.) (Incl. 151) |
| | 34036 | Intake Valve (1/32" OS) (Incl. 151) |
| | 26073 | Washer, Flat (Use as required) |
| | 650570 | Washer, Flat (Use as required) |
| | 650691 | |
| | 650690 | Washer (Use as req., but not w/6021A screw) |
| | 650727 | Washer, Belleville Screw, 5/16-18 x 1-3/4" (Use as requi red) |
| | 650694A | , , |
| | | Screw, 5/16-18 x 2" (Use as required) |
| 130A | 6021A | Screw, 5/16-18 x 1-1/2" (Use as required, but do notuse with |
| | | 650691 washer) |
| 131 | 650802 | Screw, 1/4-20 x 5/8" (Use as required) |
| 131 | 650737 | Screw, 1/4-20 x 1/2" (Use as required) |
| 131 | 650738 | Screw, 1/4-20 x 5/8" (Use as required) |
| 131A | 650713 | Screw, 5/16-18 x 5/8" (Use as require d) |
| 131A | 792028 | Screw, 5/16-18 x 7/8" (Use as require d) |
| 135 | 33636 | Resistor Spark Plug (RJ17LM) |
| | 33369 | Bracket, Governor gear |
| | 650836 | Screw, 10-24 x 1/2" |
| | 27882 | Cap, Upper valve spring |
| | 35862 | Seal Assy., Intake valve |
| | 27881 | Spring, Valve |
| | 32581 | Cap, Lower valve spring |
| | 27896A | * Gasket, Breather cover |
| | 28423 | Body, Breather |
| | 28424 | Element, Breather |
| | 28425 | Cover, Valve spring |
| | 35350 | Tube, Breather |
| | 650128 | Screw, 10-24 x 1/2" |
| | 650597 | Screw, 10-24 x 5/8" |
| | 29752 | Nut & Lockwasher, 1/4-28 |
| | 30593 | Clip, Primer line (Use as required) |
| | 30088A | Screw, 1/4-28 x 1" |
| | 33263 | * Gasket, Carburetor |
| | 33877 | Pipe, Intake |
| | 31342 | Spring, Compression |
| | 650549 | Screw, 5-40 x 7/16" |
| | 610973 | Terminal Assy. (Use as required) |
| | 650378 | Screw, Torx T-30, 5/16-18 x 1-1/8 " |
| | 27915A | * Gasket, Intake pipe |
| | 35447A | Blower Housing (For electric starter) |
| 261 | 650788 | Screw, 5/16-18 x 3/4" (Use as require d) |
| | 29747B | Screw, 5/16-24 x 21/32" |
| | 33272B | Cover, Cylinder head |
| | 35824 | Muffler (Optional quiet muffler) |
| | 33280A | Muffler |
| | 31588 | Plate, Muffler locking |
| | 650696 | Screw, 5/16-18x2-3/4" (Used with 276A) |
| | 650729 | Screw, 5/16-18 x 3-3/16" |
| | 33013 | Cover, Starter bubble |
| | 650760 | Screw, 8-32 x 3/8" |
| | 33662 | Hub & Screen Assy., Starter |
| | 29752 | Nut & Lockwasher, 1/4-28 |
| 201 | · | |


| 290 290 290 292 298 | Part Number 29774 30705 30962 26460 650665 34156A | Qty | Fuel Line (Braided 8-1/4")(21 cm)(As req.) Fuel Line (Braided 16")(41 cm)(Use as req.) Fuel Line (Braided 32")(81 cm)(Use as req.) Clamp, Fuel line (Use as required) Screw, 1/4-15 x 7/8" Fuel Tank (Incl. 292 & 301) NOTE: These tanks were builtwith different size fuel inlet openings. Tanks with the 1-3/16" I.D. opening use fuel cap 34210. Tanks with the 1-1/2" I.D. opening use fuel cap 35355. |
|--|--|-----|---|
| | 410144B 33032 | | Fuel Cap (White Plastic)(Std)(1-1/2" I.D.) Fuel Cap (Red Plastic) (Spurt Resistant, Low Profile) (1-3/16" I.D.) |
| 301 | 34210 | | Fuel Cap (Red Plastic) (Spurt Resistant, High Profile) (1-3/16" I.D) |
| 305 306 310 325 325 336 337 338 340 341 342 359 360 364 365 370J 379 | 35355 33893A 33590 34011A 29443 34246 650765 34666 28942 34154 34155 650561 34141 32576 33377 650767 34870 631021 632111 | | Fuel Cap (Red plastic) (1-1/2" I.D.) Tube, Oil fill "O" Ring Dipstick (Incl. 306) Clip, Fuel line (Use as required) Clip, Ground wire (Use as required) Screw, 10-32 x 1/2" Cover, Carburetor Screw, 10-32 x 3/8" Plate, Fuel tank mounting Bracket, Fuel tank mounting Screw, 1/4-20 x 5/8" Guard, Starter Seal, Snow guard Bracket, Carburetor cover mounting Screw, 8-32 x 27/64" Decal, Instruction Can be used on HM80 with diecast starter. Inlet Needle, Seat & Clip Assy. Carburetor (Incl. 184) (Refer to Division 5, Section A, page 170 for breakdown or Fiche18A-1, Grid F-1) |
| 390 | 590479 | | Rewind Starter (Refer to Division 5, Section C, page 30 for breakdown or Fiche 18A-1, Grid G-5) |
| | 33279G 35570 | | Gasket Set (Incl. items marked*) Screen Seal (Can be used on HM80 with stamped steel recoil starter) |
| 409 | 35569 | | Spacer (Can be used on HM80 with stamped steel recoil starter) |
| 410 | 730573 | | Debris Screen Kit (Incl. 360, 370B, 387, 411 &413) (Can be used on HM80 with stamped steel recoil starter) |
| 411 | 35568 | | Debris Screen (Can be used on HM80 with stamped steel recoil starter) |
| 413 | 650907 | | Screw, 5/16-18 x 1-5/8" (Can be used on HM80 with stamped steel recoil starter) |
| 421 | 730225 730226 730572 | | SAE 30, 4-Cycle Engine Oil (Quart) SAE 5W30, 4-Cycle Engine Oil (Quart) Starter Muff Kit (Incl. 370J, 426 & 427) (Can be used on HM80 with die cast starter) |

| Ref # | Part Number | | Description |
|-------|-------------|---|---|
| 429 | 650868 | | Screw, 8-18 x 1-1/8" (3 Required) (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 430 | 611077 | | Alternator, Add on (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 431 | 590609 | | Centering tube (Use with engines equipped with die cast aluminum starter)(Use as required) (Refer to Mechanics Handbook for installation instructions) |
| 431 | 590610 | | Centering tube (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 432 | 611078 | | A.C. Lighting Connector (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 432 | 611079 | | D.C. Charging Connector (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 433 | 590611 | | Alternator Shaft (4.00") (Use with engines equipped with cast aluminum starter)(Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 433 | 590636 | : | Alternator Shaft (Use with engines equipped with stamped steel starter)(Use as required) (Refer to Mechanics Handbook for installation instructions). |



| 62 63 74 97 131 131 131 174 | Part Number 650760 28545 31855 650802 650737 650738 650128 650597 730127 | Qty | Description Screw, 8-32 x 3/8" Grommet, Plastic Retainer, Bearing Lockwasher, Heavy split, #10 (Buy loc ally) Screw, 1/4-20 x 5/8" (Use as required) Screw, 1/4-20 x 1/2" (Use as required) Screw, 1/4-20 x 5/8" (Use as required) Screw, 10-24 x 1/2" Screw, 10-24 x 5/8" Air Cleaner Ass'y. (Incl.238,239,240,241,243,245 & 370) (Use as required) |
|--|--|-----|---|
| 227 | 730164 | | Air Cleaner Ass'y. (Incl. 238, 239, 240, 241, 243 & 245) (Use as required) |
| | 650824 650851 | | Stud, 1/4-20 x 7.33 (Use as required) Stud, 1/4-20 x 8.1 (Use as required) (Used with drilled thru elbow) |
| 274 | 34700 35865 391026 | | Element, Air cleaner Gasket, Exhaust (Use as required) Muffler (Incl. 284, 284A & 416A) (This spark arresting muffler can be used on any model.) |
| 277 277A 292 298 369 370J | 35824 650729 650696 26460 650665 35857 34870 34387 | | Muffler (Optional quiet muffler) Screw, 5/16-18 x 3-3/16" Screw, 5/16-18x2-3/4" (Used with 276A) Clamp, Fuel line (Use as required) Screw, 1/4-15 x 7/8" Valve, Fuel shut-off Decal, Instruction Can be used on HM80 with diecast starter. Decal, Instruction Can be used on HM80 with stamped steel recoil starter. |
| 395 | 33329D | | Starter Motor Kit (110-120 Volt) This 110-120 volt starter motor kit may have been added to this engine. It can be added only if cylinder hasdrilled and tapped starter mounting bosses and a ring gear flywheel. Refer to service number stamped on end cap of motor, or on decal for identification. Ref |
| 408 | 35570 | | Screen Seal (Can be used on HM80 with stamped steel recoil starter) |
| 409 | 35569 | | Spacer (Can be used on HM80 with stamped steel recoil starter) |
| 410 | 730573 | | Debris Screen Kit (Incl. 360, 370B, 387, 411 &413) (Can be used on HM80 with stamped steel recoil starter) |
| 411 | 35568 | | Debris Screen (Can be used on HM80 with stamped steel recoil starter) |
| 413 | 650907 | | Screw, 5/16-18 x 1-5/8" (Can be used on HM80 with stamped steel recoil starter) |
| | 730130 730572 | | Exh.Adapter Kit (Incl.274,277)(Use as req.) Starter Muff Kit (Incl. 370J, 426 & 427) (Can be used on HM80 with die cast starter) |
| 429 | 650868 | | Screw, 8-18 x 1-1/8" (3 Required) (Use as required) (Refer to Mechanics Handbook for installation instructions). |

| Ref # | Part Number | Qty | Description |
|-------|-------------|-----|---|
| 430 | 611077 | | Alternator, Add on (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 431 | 590609 | | Centering tube (Use with engines equipped with die cast aluminum starter)(Use as required) (Refer to Mechanics Handbook for installation instructions) |
| 431 | 590610 | | Centering tube (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 432 | 611078 | | A.C. Lighting Connector (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 432 | 611079 | | D.C. Charging Connector (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 433 | 590611 | | Alternator Shaft (4.00") (Use with engines equipped with cast aluminum starter)(Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 433 | 590636 | | Alternator Shaft (Use with engines equipped with stamped steel starter)(Use as required) (Refer to Mechanics Handbook for installation instructions). |



| Ref # | Part Number (| Qty Description |
|-------|---------------|---|
| | 650760 | Screw, 8-32 x 3/8" |
| | 650516 | Screw, 1/4-20 x 1-1/8 |
| | | |
| 100 | 610982 | Magneto (w/ring gear) (12 Volt, 3 Amp) NOTE: The |
| | | complete magneto is not available as an assembly. The |
| | | magneto number is shown for reference purposes only. Order |
| | | component parts individually, as shown in parts list. (Refer to |
| | | Division 5, Section B, page 36 for breakdown or Fiche 18A-1, |
| | | Grid G |
| 400 | 0.4505 | D 1 4 01 1 |
| | 34587 | Bracket, Choke |
| | 34667 | Link, Governor |
| 200A | 34677 | Control Bracket (Incl.19,19A,203,204, 206,209) |
| 203 | 31342 | Spring, Compression |
| 204 | 650549 | Screw, 5-40 x 7/16" |
| 206 | 610973 | Terminal Assy. (Use as required) |
| | 33878 | Link, Governor-to-throttle |
| | 650821 | Screw, 10-32 x 1/2" |
| | 32410 | Knob, Control |
| | 34586 | |
| | | Rod, Choke |
| | 35438 | Knob, Control |
| | 28820 | Screw, 10-32 x 1/2" |
| | 35447A | Blower Housing (For electric starter) |
| | 35824 | Muffler (Optional quiet muffler) |
| | 650696 | Screw, 5/16-18x2-3/4" (Used with 276A) |
| 286B | 33662 | Hub & Screen Assy., Starter |
| 290 | 29774 | Fuel Line (Braided 8-1/4")(21 cm)(As req.) |
| 290 | 30705 | Fuel Line (Braided 16")(41 cm)(Use as req.) |
| 290 | 30962 | Fuel Line (Braided 32")(81 cm)(Use as req.) |
| | 410144B | Fuel Cap (White Plastic)(Std)(1-1/2" I.D.) |
| | 33032 | Fuel Cap (Red Plastic) (Spurt Resistant, Low Profile) (1-3/16" |
| 00. | 3332 | I.D.) |
| | | • |
| 301 | 34210 | Fuel Cap (Red Plastic) (Spurt Resistant, High Profile) |
| | | (1-3/16" I.D) |
| 201 | OFOEF | Fuel Cap (Bad plactic) (4.4/0" LD.) |
| | 35355 | Fuel Cap (Red plastic) (1-1/2" I.D.) |
| | 33876 | Gasket, Stator |
| | 35038 | Spacer, Tank |
| | 34155 | Bracket, Fuel tank mounting |
| 342 | 650561 | Screw, 1/4-20 x 5/8" |
| 350 | 570682 | Primer Assy. |
| 351 | 32180C | Primer Line |
| 370B | 34387 | Decal, Instruction Can be used on HM80 with stamped steel |
| | | recoil starter. |
| | 0.4070 | |
| | 34870 | Decal, Instruction Can be used on HM80 with diecast starter. |
| | 30547A | Contact Assy., Breaker |
| | 610767A | Condenser |
| 408 | 35570 | Screen Seal (Can be used on HM80 with stamped steel |
| | | recoil starter) |
| 400 | 25560 | Change (Can be used an LIMO) with stamped steel resell |
| 409 | 35569 | Spacer (Can be used on HM80 with stamped steel recoil |
| | | starter) |
| 410 | 730573 | Debris Screen Kit (Incl. 360, 370B, 387, 411 &413) (Can be |
| 710 | . 555. 5 | used on HM80 with stamped steel recoil starter) |
| | | · |
| 411 | 35568 | Debris Screen (Can be used on HM80 with stamped steel |
| | | recoil starter) |
| | | |

| | Part Number | Qty | Description |
|-----|-------------|-----|---|
| 413 | 650907 | | Screw, 5/16-18 x 1-5/8" (Can be used on HM80 with stamped steel recoil starter) |
| 425 | 730572 | | Starter Muff Kit (Incl. 370J, 426 & 427) (Can be used on HM80 with die cast starter) |
| 429 | 650868 | | Screw, 8-18 \times 1-1/8" (3 Required) (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 430 | 611077 | | Alternator, Add on (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 431 | 590609 | | Centering tube (Use with engines equipped with die cast aluminum starter)(Use as required) (Refer to Mechanics Handbook for installation instructions) |
| 431 | 590610 | | Centering tube (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 432 | 611078 | | A.C. Lighting Connector (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 432 | 611079 | | D.C. Charging Connector (Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 433 | 590611 | | Alternator Shaft (4.00") (Use with engines equipped with cast aluminum starter)(Use as required) (Refer to Mechanics Handbook for installation instructions). |
| 433 | 590636 | | Alternator Shaft (Use with engines equipped with stamped steel starter)(Use as required) (Refer to Mechanics Handbook for installation instructions). |