


| Ref # | Part Number Q | ty Description  |
|-------|---------------|---|
| 1     | 33729A        | Cylinder (Incl. 2 & 20) (2-13/16" Bor e)                    |
|       | 26727         | Pin, Dowel  |
|       | 33734         | Element, Breather   |
|       | 34214A        | Breather Ass'y. (Incl. 6, 8, 9 & 12)                        |
|       |               |   |
|       | 33735         | * Gasket, Breather  |
|       | 30200         | Screw, 10-24 x 9/16"  |
|       | 33886         | Tube, Breather  |
|       | 28277         | Washer, Flat  |
| 15    | 30589         | Rod, Governor (Incl. 14)                                    |
| 16    | 32651         | Lever, Governor   |
|       | 31335         | Clamp, Governor (Clamp is positioned towardsspark plug end  |
|       |               | on 1977-78 and latermodels. It is positioned opposite spark |
|       |               | plugend on earlier models.)                                 |
|       |               | plugeria ori earlier models.)                               |
| 18    | 650548        | Screw, 8-32 x 5/16"   |
| 19    | 31386         | Spring, Governor  |
|       | 32600         | Seal, Oil   |
|       | 33838         | Crankshaft Ass'y.   |
|       |               |   |
| 32    | 32323         | Washer, Thrust NOTE: This thrust washer maynot be           |
|       |               | required if a new crankshafthas been installed. Check the   |
|       |               | proper Mechanic's Handbook for acceptable end play. Use     |
|       |               | this .010" thrust washer if excess end play is measured.    |
| 40    | 34535         | Piston, Pin & Ring Set (Std.) (2-13/1 6")                   |
|       |               |   |
|       | 34536         | Piston, Pin & Ring Set (.010" OS)                           |
|       | 34537         | Piston, Pin & Ring Set (.020" OS)                           |
|       | 33562B        | Piston & Pin Ass'y.(Std)(Incl. 43)(2- 13/16")               |
|       | 33563B        | Piston & Pin Ass'y. (.010" OS) (Incl. 43)                   |
| 41    | 33564B        | Piston & Pin Ass'y. (.020" OS) (Incl. 43)                   |
| 42    | 33567         | Ring Set (Std.) (2-13/16" Bore)                             |
|       | 33568         | Ring Set (.010" OS)   |
|       | 33569         | Ring Set (.020" OS)   |
|       | 20381         | Ring, Piston pin retaining                                  |
|       | 32875         | Rod Assy., Connecting (Incl. 18)                            |
|       |               |   |
|       | 32609         | Plate, Lock (Do not use with No. 32610A locking type bolt.) |
|       | 32610         | Bolt, Connecting rod (Early Productio n)                    |
|       | 32610A        | Bolt, Connecting rod  |
|       | 27241         | Lifter, Valve   |
| 50    | 33154         | Camshaft  |
| 52    | 29914         | Pump Assy., Oil   |
| 69    | 35261         | * Gasket, Mounting flange                                   |
|       | 32612A        | Flange Ass'y. (Incl. 72, 75 & 80)                           |
|       | 30572         | Plug, Oil drain (Incl. 73)                                  |
|       | 9556          | Plug, Pipe  |
|       | 28833         | * Drain Plug Gasket(Not used w/ plastic plug)               |
|       | 27897         |   |
|       |               | Seal, Oil   |
|       | 30574         | Shaft, Mechanical governor                                  |
|       | 30590A        | Washer, Flat  |
|       | 30591         | Gear Assy., Governor (Incl. 81)                             |
|       | 30588A        | Spool, Governor   |
| 84    | 29193         | Ring, Retaining   |
|       | 650488        | Screw, 1/4-20 x 1-1/4"                                      |
|       | 610951        | Key, Flywheel   |
|       | 650815        | Washer, Belleville  |
|       | 650607        | Nut, Flywheel   |
|       |               |   |
|       | 27276         | Cover, Spark plug   |
|       | 650489        | Screw, 1/4-20 x 5/8"  |
|       | 35349         | Wire, Ground  |
| 119   | 33554A        | * Gasket, Cylinder head                                     |
|       |               |   |

|     | Double of an   | N. Baradata  |
|-----|----------------|--|
|     |                | Qty Description  |
|     | 33016A         | Head, Cylinder (Incl. 131)                                 |
|     | 32644A         | Intake Valve (Std.) (Incl. 151) (Inverted Ports)           |
|     | 32645A         | Intake Valve (1/32" OS) (Incl. 151) (Inverted Ports)       |
|     | 29313C         | Exhaust Valve (Std.) (Incl. 151) (Inverted Ports)          |
|     | 29315C         | Exhaust Valve (1/32" OS) (Incl. 151) (Inverted Ports)      |
|     | 26073          | Washer, Flat (Not used on late produc tion)                |
|     | 650691         | Washer, Flat (Use as required)                             |
|     | 650818         | Screw, 5/16-18 x 1-1/2" (Use as requi red)                 |
|     | 6021A          | Screw, 5/16-18 x 1-1/2" (Use as required)                  |
|     | 650694A        | Screw, 5/16-18 x 2" (Use as required)                      |
|     | 33636          | Plug, Spark (J-8C)   |
|     | 31671          | Upper Cap (Int. & Ex.)(Early Producti on)                  |
|     | 33678          | Cap, Upper valve spring (Exhaust)                          |
|     | 31672<br>31673 | Spring, Valve  |
|     | 27234A         | Cap, Lower valve spring                                    |
|     | 32755          | * Gasket, Valve spring cover                               |
|     | 650128         | Cover, Valve spring box                                    |
|     | 29752          | Screw, 10-24 x 1/2"  |
|     | 30593          | Nut & Lockwasher Assy.<br>Clip, Magneto wire               |
|     | 6201           | Screw, 1/4-28 x 7/8"                                       |
|     | 33739          | Pipe, Intake   |
|     | 32653          | Link, Governor spring                                      |
|     | 32181A         | Speed Control (Incl. 203, 204 & 206)                       |
|     | 31342          | Spring, Compression  |
|     | 650549         | Screw, 5-40 x 7/16"  |
|     | 610973         | Terminal Assy. (Use as required)                           |
|     | 33133          | Link, Throttle   |
|     | 34336          | Link, Throttle   |
|     | 30200          | Screw, 10-24 x 9/16"                                       |
|     | 27793          | Clip, Conduit  |
|     | 28942          | Screw, 10-32 x 3/8"  |
|     | 650142         | Screw, 1/4-20 x 1-1/8"                                     |
|     | 33751A         | * Gasket, Intake   |
|     | 28820          | Screw, 10-32 x 1/2"  |
| 239 | 27272A         | * Gasket, Air cleaner                                      |
|     | 31715          | Body, Air cleaner  |
|     | 31691          | Bracket, Air cleaner                                       |
| 243 | 650152         | Screw, 8-32 x 3/8"   |
| 244 | 730164         | Cleaner Kit (Incl. 238 thru 245 & 370 B) (Use as required) |
| 246 | 31700          | Element, Air cleaner                                       |
| 260 | 33738D         | Housing, Blower NOTE: Replacement hardware may differ      |
|     |                | when servicing starter assy. or blower housing. Refer to   |
|     |                | Service Bulletin 508.                                      |
| 261 | 650561         | Screw, 1/4-20 x 5/8"                                       |
|     | 26754A         | * Gasket, Exhaust (Use as required)                        |
|     | 33670A         | * Gasket, Exhaust  |
|     | 35771          | Muffler (Incl. 274)  |
|     | 650774         | Screw, 1/4-20 x 2-3/8"                                     |
|     | 30063          | Screw, 1/4-20 x 1/2" (Use as required )                    |
|     | 33667          | Cup, Starter   |
|     | 33668          | Screen, Starter cup  |
|     | 29752          | Nut & Lockwasher 1/4-28 (Use as requi red)                 |
|     | 29774          | Fuel Line (Braided 8-1/4") (21 cm)                         |
|     | 30705          | Fuel Line (Braided 16") (40 cm)                            |
|     | 33754          | Line, Fuel (Metal 3.360")                                  |
|     | 26460          | Clamp, Fuel line   |
|     |                | 1),  |

| Ref #                                   | Part Number   | Qty Description  |
|---|---|--|
| 301<br>301                              | 32671<br>410144B<br>33032<br>34282                                    | Tank Assy., Fuel (Incl. 292 & 301) Cap, Fuel (Standard) (Use as required) Cap, Fuel (Use as required) "O" Ring (This "O" ring is required with metal fill tube only when replacement mounting flange with .777 dia. oil fill hole has been used.)  |
| 312<br>313<br>325<br>325<br>370<br>370C | 27625<br>29673<br>33876<br>27275<br>33685<br>34346<br>35344<br>610942 | Plug, Oil filler (Incl. 312)  * Gasket, Filler plug Gasket, Stator Clip, Wire retaining Clip, Wire retaining (Early Productio n) Decal, Instruction Decal, Speed control Magneto NOTE: The complete magneto is not available as an assembly. The magneto number is shown for reference purposes only. Order component parts individually, as shown in parts list. (Refer to Division 5, Section B, page 30 or Fiche 6 Grid F-12 for breakdown) |
| 378<br>379                              | 30547A<br>30548B<br>631021<br>631716                                  | Contact Assy., Breaker Condenser Inlet Needle, Seat & Clip Assy. Carburetor (Incl. 184) (Refer to Division 5, Section A, page 122 or Fiche 6 Grid E-7 for breakdown)   |
| 390                                     | 590420  | Starter, Rewind NOTE: Replacement hardware may differ when servicing starter assy. or blower housing. Refer to Service Bulletin 508. (Refer to Division 5, Section C, page 25 or Fiche 6, Grid G-3 for breakdown)  |
|   | 33740D<br>730225  | * Gasket Set (Incl. items marked *)<br>SAE 30, 4-Cycle Engine Oil (Quart)  |



| Rof # | Part Number | Qty | Description   |
|-------|-------------|-----|---|
|       | 650815      | Qιy | Washer, Belleville  |
|       | 650607      |     | Nut, Flywheel   |
|       | 28820       |     | Screw, 10-32 x 1/2"   |
|       | 650561      |     | Screw, 1/4-20 x 5/8"  |
|       | 26754A      |     | * Gasket, Exhaust (Use as required)   |
|       | 33670A      |     | * Gasket, Exhaust   |
|       | 391026      |     | Muffler (Incl. 284, 284A & 414A) (This spark arrester mufflercan be used on any model with a 3/4-14 tapped exhaust port.)                                   |
| 277   | 650774      |     | Screw, 1/4-20 x 2-3/8"  |
| 277   | 30063       |     | Screw, 1/4-20 x 1/2" (Use as required )   |
| 284A  | 650578      |     | Screw, 8-18 x 3/8" (Use as required)  |
| 284   | 33700       |     | Cover & Tube, Muffler (Use as require d)  |
| 285   | 33667       |     | Cup, Starter  |
| 287   |             |     | Pop Rivet(Purchase locally)(Use as re quired)   |
| 414A  | 33323       |     | Screen, Muffler (Use as required)   |
| 415   | 730162      |     | Muffler Adapter Kit (Incl. 121 & 128) (Conventional Ports)  |
| 415   | 730165      |     | Muffler Adapter Kit (Incl. 274 & 277) NOTE: This muffler adapter can be used only on models which have exhaust port on top (above intake). (Inverted Ports) |
| 1113  |             |     | Rivet, Open end (Can be purchased loc ally)   |