


Page 1 of 9

	Part Number	Qty	
2 2 2 2 2 2 4	33762B 31927 28483 9556 28534 27652 34445A		Cylinder (Incl. 2, 4 & 33) (3-5/16" B ore) Pipe Plug, 3/8-18 sq. head (Use as re quired) Pipe Plug (3/8-18 hex countersunk) (A s req.) Pipe Plug (3/4-14 sq.hd.)(As req.)(Bu y local) Pipe Plug (1/8-27 sq. hd.) (Use as re quired) Pipe Plug(1/8-27 hex c/sunk headless) (As req) Pin, Dowel Crankshaft (Incl. 6 thru 9) NOTE: When using this crankshaft to repair older units equipped with straight cut cam and governor gears, it will be necessary to order 34751 helical governor gear assembly and 34752 helical camshaft in order to the complete the repair.
$\begin{array}{c} 7\\ 8\\ 9\\ 11\\ 11\\ 11\\ 11\\ 11A\\ 11A\\ 11A\\ 11A\\$	29783 31931 31932 31928 34508 34509 34510 32001C 32002B 32003B 31919 32004 32005 32006 33093A 34383 34384 32077 26073 28264 33470 33472 33471 33505 33645 33506 33646 33507 33508 33509 34410 33510 33473 650745 35479 30590A 31948 31956B		
33 34 35 36 37	32580A 31950 650451 650588 32425 32426 29193		Cylinder Cover Assy.(Incl.2,33,36,37 & 38) * Seal, Oil Screw, 1/4-20 x 1" Screw, 1/4-20 x 2" Rod Assy., Governor Spacer, Governor rod Ring, Retaining

	Ded N. school		
	650128		rew, 10-24 x 1/2"
	34225A		Sasket, Cylinder head
	33763		ad, Cylinder
	35552		ark Plug (RL-82C)
	650691		asher, Flat
	650690		asher, Belleville
	650746		rew, 5/16-18 x 1-3/8"
	650692		rew, 5/16-18 x 1-3/4"
	730218	Val	Ive Guide Kit (Incl. 49)
49	792035	Rin	ng, Retaining
50	33515A	* G	Gasket, Intake pipe
51	33475	Pip	be, Intake
52	650378	Scr	rew, Torx T-30, 5/16-18 x 1-1/8"
53	792028	Scr	rew, 5/16-18 x 7/8"
54	33476A	* G	Sasket, Carburetor
55	34285	Baf	iffle, Air extension
56	792075	Nut	it, Lock 5/16-24 (Used in early prod uction)
57	33478		ik, Governor lever-to-throttle leve r
58	31963	Lev	ver, Governor
	31964		amp, Governor lever
	650518		ckwasher, No. 10 E.T.
	30312		rew, 10-32 x 1/2"
	650544		rew, Torx T-25, 10-24 x 7/8"
	7975		ıt, 10-24
	31965		ate, Governor spring
	31984A		ver Assy., Control
	28558		asher, Wave
	31966		shing, Governor lever
	650597		rew, 10-24 x 5/8"
	31967		ring, Governor
	650591		rew, 10-24 x 2"
	33099		ring
	32599		" Ring (Incl. in 251)
	650615		asher, Flat
	32579		iffle, Blower housing
	650561		rew, 1/4-20 x 5/8"
	650592		y, Flywheel
	730201		gger Pin Kit (Use as required)
	610909	-	wheel
	650616	•	it, Flywheel
	610906		lid State Magneto (Incl. 158 thru 1 61)
	650661		rew, 1/4-20 x 3/4"
	30063		rew, 1/4-20 x 3/4 rew, 1/4-20 x 1/2"
	650751		rew, 1/4-20 x 1/2 rew, 1/4-20 x 7/16"
	34195B		ower Hsg.(Incl.218,219)(For elec.st arter)
	8274		S (1 ,
	8274		asher, Lock
			asher, Lock
	650595		rew, 5/16-24 x 3/8"
	650595		rew, 5/16-24 x 3/8"
	650752 25475		rew, 1/4-20 x 7/16"
	35475		be, Push rod
	33481		O" Ring (Also Incl. in 251)
	34754		ousing, Rocker arm
	33484		O" Ring (Also Incl. in 251)
	650168		asher, Flat
	32610A		rew, 1/4-20 x 29/32"
	33485		m, Rocker
98	33486	Rin	ng, Retaining

		Qty	Description
	650755		Screw, 1/4-20 x 3/4"
	650864		Nut, Hex, 1/4-20
	650756		Stud, Rocker arm
102	33487		* "O" Ring (Also Incl. in 251)
103	33488		Cover, Rocker arm
104	31958A		* Gasket, Breather (Also Incl. in 251)
105	33489		Body Assy., Breather
	33490		Tube, Breather
	30102		* Screw, 10-32 x 5/8" (Also Incl. in 25 1)
	650738		Screw, 1/4-20 x 5/8"
	35471		
			* Gasket, Air cleaner
	650399		Screw, 10-32 x 5/8"
	32008		Element, Air cleaner
	650513		Nut, Wing
	8345		Washer, Flat
119	32426		Spacer, Screen
120	32953		Screen
122	650670		Screw, 1/4-20 x 3/4"
	27070		Washer, Lock
	650675		Washer, Flat
	32577		Cover, Cylinder NOTE: Determine the gap between the cover
110	02011		and the machined surface on the cylinder, which can be
			from .001" up to .007", in which case no shim gaskets will be
			required. Use of gaskets must be limited to a combined total
			of .010" thick. Steel spacersmust be used as required to eli
147	792028		Screw, 5/16-18 x 7/8"
	31971		* Gasket, Shim (.004/.005 thick) NOTE: Determine the gap
100			between the cover and the machined surface on the
			cylinder, which can be from .001" up to .007", in which case
			no shim gaskets will be required. Use of gaskets must be
			limited to a combined total of .010" thick. Steel
			spacersmust be used a
156	31972		* Gasket, Shim (.005/.007 thick) NOTE: Determine the gap
			between the cover and the machined surface on the
			cylinder, which can be from .001" up to .007", in which case
			no shim gaskets will be required. Use of gaskets must be
			limited to a combined total of .010" thick. Steel
			spacersmust be used a
			spacersinusi be used a
157	32031		* Spacer, Steel (.010 thick) NOTE: Determine the gap
			between the cover and the machined surface on the
			cylinder, which can be from .001" up to .007", in which case
			no shim gaskets will be required. Use of gaskets must be
			limited to a combined total of .010" thick. Steel
			spacersmust be used as re
			opartionities de loca do le
158	610118		Cover, Spark plug
159	610750		Grommet, Lead wire
	610408		Nut, 8-32
	610908		Terminal, Female
	32252		Shaft, Flywheel extension
	27513		•
			Lockwasher, Split
	792051		Screw, 1/4-20 x 1-3/4"
	33068		Dipstick (Incl. 190)
	29985		"O" Ring
	32352		Tube, Oil filler
	29673		* Gasket, Oil filler tube
244	34346		Decal, Instruction

Ref # Part Number	Qty Description
244A 550223	Decal, Name
246 632024	Valve, Seat & Spring Assy.
247 631718A	Carburetor (Incl. 54 & 246) (Refer to Division 5, Section A, page 124 for breakdown)
250 33516G	* Gasket Set (Incl. items marked *)
251 35075	"O" Ring Kit (Incl. Nos. items marked +)



		/ Description
	650128	Screw, 10-24 x 1/2"
	34284	Cover, Cylinder head
	34283	Cover, Cylinder head
82	30063	Screw, 1/4-20 x 1/2"
126A	35731	Muffler (Incl. 126B)
141		Gear, Counterbalance weight (Straight teeth) (For replacement see Ref. 132. Order correct kit for your enginemodel number.)
148	610902	Alt.Coil Ass'y. (Incl.162,163,163A) (20 amp)
	650521	Screw, 10-32 x 1-1/8"
	610996	Regulator (20 Amp) (Incl. 212 thru 21 8)
153	792028	Screw, 5/16-18 x 7/8"(Use w/32817 str .motor)
153	650781	Screw,5/16-18 x 11/16"(Use w/33835 st r.motor)
162A	610903	Connector, Flat
163A	610905	Terminal
163	610904	Terminal
209	730178	Ech.Adapter Kit (Incl.210 & 211)(As r equired)
	34102B	Gasket, Exhaust (Use as required)
	30196	Screw, 5/16-18 x 3/4" (Use as require d)
	610990	Connector, Male
	610921	Connector
	610922	Terminal
	610989	Terminal
	610992	Terminal, Female
	610991	Terminal, Female
	30063	Screw, 1/4-20 x 1/2"
238	730212	Adapter Plate Kit (Optional) NOTE: If you are having mounting problems in using a HH100 thru0H180 inplace of a large frame competitivebrand, we would like to call your attention to 730212 adapter plate kit. The kit converts the bottom mounting system found on HH100 thru 0H180 to a top mounting sys
249	33835	Electric Starter Motor (12-Volt) (Refer to Division 5, Section D for breakdown)


1714

145

143

1710 196

ILLUSTRATION SHOWS TYPICAL PARTS ONLY. ORDER BY PART NUMBER. PARTS NOT LISTED ARE SUPPLIED BY DEM.



119Á

122

122A

Ref #	Part Number Qty	Description
114	650399	Screw, 10-32 x 5/8"
115	32008	Element, Air cleaner
117	650513	Nut, Wing
119	32426	Spacer, Screen
122	650670	Screw, 1/4-20 x 3/4"
123	27070	Washer, Lock
123	650675	Washer, Flat
143	29774	Fuel Line (Braided 8.25")(21 cm)(As r equired)
143	30705	Fuel Line (Braided 16")(41 cm)(As req uired)
143	30962	Fuel Line (Braided 32")(81 cm)(As req uired)
144	35018	Pump, Impulse fuel
145	33010	Repair Kit, Impulse fuel pump
171B	32958	Fitting, Fuel pump
178	410144B	Fuel Cap (White Plastic)(Std)(As requ ired)
178	34210	Fuel Cap (Red Plastic) (Spurt resistant, High profile) (Use as required)
		. ,
	26460	Clamp, Fuel line (Use as required)
	34193	Cover, Air cleaner
	34194A	Tube, Air cleaner
	35473	Bracket, Air cleaner
	34197	Gasket, Air cleaner
245	730134	Rewind Starter Kit (Incl.120A, 121, 122, 187, 188 & 248) (Use as required)